

KD6G



Refrigerated display -22/+5°C Luxor Classic Slim

Display compartment in tempered glass throughout, externally screen-silk printed. Glass door with invisible full-height handle. LED lighting. Lower structure in special anti-fingerprint steel. Integrated wheels. Electronic p.c.b. HACCP alarms. Ventilated refrigeration with evaporator positioned on the top of the display compartment, anti-condense heating elements, automatic defrosting by hot gas.



General information

Supplier/producer 's name	SAGI
Series	Luxor Classic
Supplier's model identifier	KD6G
Category	upright refrigerated display units
Type	refrigerated display unit
Line	catering - pastry&bakery - ice-cream

Technical features

Temperature ranges, °C	-22/+5
Relative humidity (%)	65÷40%
Energy Efficiency Class	D
Energy consumption/year, kWh/a	6308
Method for energy consumption	EN 23953
Volume, gross, lt	324
Climate class	4 (+30°C, 55% R.H.)
Refrigerant/GWP	R290/3
LWA dB(A)	70
Cooling system	ventilated refrigeration system
Defrosting	automatic defrosting by hot gas
Evaporation of condense drain	automatic
Refrigeration power -23,3°C W	931
Frequency/voltage	230V 1N~ / 50Hz
Electric power, kW	1,25

Refrigerated display -22/+5°C Luxor Classic Slim



Construction features

Display compartment	compartment in tempered glass throughout, grey screen-silk printed glass, anti-condense heating elem.
Lower structure	special grey anti-fingerprint steel
LED lighting	high luminous intensity anti-glare LED bars, front panel on the back of the door
Door	1 glass door
Standard hinging door	on the right / no-reversible on the site (contact the manufacturer for the left door)
Door handle	"invisible" full-height
Internal structure	AISI 304 stainless steel grid-supporting rack
Evaporator	positioned on the top of the display compartment with AISI 304 stainless steel structure
Easymaintenance	accessibility to all the functional and control components - clip clap system
Safety interlock switch	yes, to stop internal fan
Feet	nr.4 integrated wheels, hidden by the structure

Control and functions

Kinf of control	electronic pannel control board
Display	digital
Alarms	optical and acoustical
Functions/programs	it is possible to lock keys

Standard

Shelf (n.)	5
Shelf's dimensions (cm)	49x47
Shelf loading capacity (kg)	12 (available the accessoire KSR25KGP: front bearing kit for shelves, to load up to 25 kg)

Dimensions and weights

Packing (LxDxH), cm	74x76x202
Dimensions (LxDxH), cm	60x64,5x184
Gross Weight (kg)	236
Net Weight (kg)	217

Notes

Notes	installation allowed to an altitude up to 800 meters above sea level (contact the company)
-------	--