## KIGC2



## Refrigerated counter-GN1/1-AISI 304-I-green

One-piece AISI 304 stainless steel body.Temperature ranges: -2/+10°C.Without top.Depth 70 cm.GN 1/1.With doors and drawers.Control panel with digital thermometer - thermostat and communication port. Automatic defrosting electric type.



( (

#### **General information**

Series	l-green
Supplier's model identifier	KIGC2
Category	counter cabinet
Туре	refrigerated counter
Line	catering - GN 1/1

### **Technical features**

chinear reacares	
Temperature ranges, °C	-2/+10
Energy Efficiency Class	В
Energy consumption, kWh/24h	2,42
Energy consumption/year, kWh/a	885
Method for energy consumption	EN 22041
Energy Efficiency Index	34,7
Net usable volume, lt	298
Volume, gross, lt	578
Climate class	5 (+40°C, 40% R.H.)
Heavy duty cabinets	This appliance is intended for use in ambient temperatures up to 40 °C
Refrigerant/GWP	R290/3
Refrigerant charge, kg	0,08
LWA dB(A)	50
Cooling system	ventilated refrigeration system. U- flow air circulation to assure peak cooling unit reliability
Defrosting	automatic by heating elements
Evaporation of condense drain	automatic

Refrigerated counter-GN1/1-AISI 304-I-green





# KIGC2



Refrig	eration power at -10°C W	560
Frequ	ency/voltage	230V 1N~ / 50Hz
Electr	ic power, kW	0,28
Construc	tion features	
Struct	ure	one-piece structure with rounded internal corners
Exterr	nal material	AISI 304 stainless steel
Intern	al material	AISI 304 stainless steel
Intern	al bottom	with rounded corners
Insula	tion thickness, mm	60
Workt	ор	without worktop
Intern	al structure	AISI 304 stainless steel grid-supporting rack
Positio	ons (n.)/spaced, mm	11/40,5
Evapo	rator	with an anti-corrosion treatment
Easym	naintenance	the cooling unit pulls out to simplify routine cleaning of the condenser
Feet		stainless steel AISI 304, adjustable in height
Heigh	t of feet, mm	140 ÷ 200
Equip	ped with	door and drawers
Drawe	ers, type: 1/2	2
Control a	and functions	
Kinf o	f control	digital thermometer/thermostat and communication port
Displa	ry	digital
Standard	I	
Shelf's	s dimensions, cm	32,5x53 GN1/1
Shelve	es and couple of guides	complete with 1 pair of AISI 304 stainless steel runners and 1 plastic-coated shelf GN1/1 per sectio
Dimensio	ons and weights	
Packir	ng (LxDxH), cm	235,5x75,5x90
Dimer	nsions (LxDxH), cm	230x70x84
Gross	Weight (kg)	154
Net W		139

Refrigerated counter-GN1/1-AISI 304-I-green

