

# KP6GSX



## Refrigerated display +2/+10°C Luxor Classic Slim

Display compartment in tempered glass throughout, externally screen-silk printed. Glass door with invisible full-height handle. Hinge positioned on the left side. LED lighting. Lower structure in special anti-fingerprint steel. Integrated wheels, hidden by the structure. Electronic p.c.b. HACCP alarms. Ventilated refrigeration. Automatic defrosting by air.



### General information

Supplier/producer 's name	SAGI
Series	Luxor Classic Slim
Supplier's model identifier	KP6GSX
Category	upright refrigerated display units
Type	refrigerated display unit
Line	catering - pastry&bakery - ice-cream

### Technical features

Temperature ranges, °C	+2/+10
Relative humidity (%)	70
Energy Efficiency Class	B
Energy consumption/year, kWh/a	1840
Method for energy consumption	EN 23953
Volume, gross, lt	324
Climate class	4 (+30°C, 55% R.H.)
Refrigerant/GWP	R290/3
LWA dB(A)	65
Cooling system	ventilated refrigeration system
Defrosting	automatic by air
Evaporation of condense drain	automatic
Refrigeration power at -10°C W	632
Frequency/voltage	230V 1N~ / 50Hz
Electric power, kW	0,36

Refrigerated display +2/+10°C Luxor Classic Slim



## Construction features

Display compartment	completely in tempered glass with grey screen-silk printed
Lower structure	special grey anti-fingerprint steel
LED lighting	high luminous intensity anti-glare LED bars, front panel on the back of the door
Door	1 glass door
Standard hinging door	on the left / no-reversible on the site
Door handle	"invisible" full-height
Internal structure	AISI 304 stainless steel grid-supporting rack
Evaporator	positioned in the lower part of the structure
Easymaintenance	accessibility to all the functional and control components - clip clap system
Safety interlock switch	yes, to stop internal fan
Feet	nr.4 integrated wheels, hidden by the structure

## Control and functions

Kinf of control	electronic pannel control board
Display	digital
Alarms	optical and acoustical
Functions/programs	it is possible to lock keys

## Standard

Shelf (n.)	5
Shelf's dimensions (cm)	49x47
Shelf loading capacity (kg)	12 (available the accessoire KSR25KGP: front bearing kit for shelves, to load up to 25 kg)

## Dimensions and weights

Packing (LxDxH), cm	74x76x202
Dimensions (LxDxH), cm	60x64,5x184
Gross Weight (kg)	191
Net Weight (kg)	171

## Notes

Notes	installation allowed to an altitude up to 800 meters above sea level (contact the company)
-------	--