

KUAM

Refrigerated counter-GN1/1-AISI 304-Universal

One-piece AISI 304 stainless steel body.Temperature ranges: 0/+10°C.Worktop 60 mm thick in AISI 304 stainless steel.Depth 70 cm.GN 1/1.2 doors.Control panel with digital thermometer thermostat.



CE

General information

| Supplier/producer 's name | SAGI |
|--------------------------------|--|
| Series | Universal |
| Supplier's model identifier | KUAM |
| Category | counter cabinet |
| Туре | refrigerated counter |
| Line | catering - GN 1/1 |
| hnical features | |
| Temperature ranges, °C | 0/+10 |
| Energy Efficiency Class | В |
| Energy consumption, kWh/24h | 2,063 |
| Energy consumption/year, kWh/a | 753 |
| Method for energy consumption | EN 22041 |
| Energy Efficiency Index | 34,21 |
| Net usable volume, lt | 161 |
| Volume, gross, lt | 290 |
| Climate class | 5 (+40°C, 40% R.H.) |
| Heavy duty cabinets | This appliance is intended for use in ambient temperatures up to 40 $^{\circ}$ |
| Refrigerant/GWP | R290/3 |
| Refrigerant charge, kg | 0,07 |
| LWA dB(A) | 46 |
| Cooling system | ventilated refrigeration system. U- flow air circulation to assure peak cooling unit reliability |
| Defrosting | automatic |

ANGELO PO GRANDI CUCINE S.p.a. con socio unico Zona Industriale Campolungo, 79/81 - 63100 Ascoli Piceno – Italy www.sagispa.it | info@sagispa.it



Refrigerated counter-GN1/1-AISI 304-Universal

KUAM



| Evaporation of condense drain | automatic |
|--------------------------------|-----------------|
| Refrigeration power at -10°C W | 465 |
| Frequency/voltage | 230V 1N~ / 50Hz |
| Electric power, kW | 0,28 |

Construction features

| Structure | one-piece structure with rounded internal corners |
|---------------------------|---|
| External material | AISI 304 stainless steel |
| Internal material | AISI 304 stainless steel |
| Internal bottom | with rounded corners |
| Insulation thickness, mm | 60 |
| Worktop | worktop 60 mm thick in AISI 304 stainless steel (8/10mm), with soundproofing lining |
| Internal structure | AISI 304 stainless steel grid-supporting rack |
| Positions (n.)/spaced, mm | 11/40,5 |
| Evaporator | with an anti-corrosion treatment |
| Easymaintenance | the cooling unit pulls out to simplify routine cleaning of the condense |
| Feet | stainless steel AISI 304, adjustable in height |
| Height of feet, mm | 140 ÷ 200 |
| Equipped with | 2 doors |

Control and functions

| Kinf of control | thermometer-thermostat |
|-----------------|------------------------|
| Display | digital |
| Alarms | optical and acoustical |

Standard

| Key-lock | optional |
|------------------------------|--|
| Shelf's dimensions, cm | 32,5x53 GN1/1 |
| Shelves and couple of guides | complete with 1 pair of AISI 304 stainless steel runners and 1 plastic-coated shelf GN1/1 per sectio |

Dimensions and weights

| F | Packing (LxDxH), cm | 146x76x90 |
|---|------------------------|-----------|
| 0 | Dimensions (LxDxH), cm | 140x70x90 |
| (| Gross Weight (kg) | 117 |
| ١ | Net Weight (kg) | 107 |

