KUB13A

106

Refrigerated counter-GN1/1-AISI 304-Universal

One-piece AISI 304 stainless steel body. Temperature ranges: 0/+10°C. Worktop 60 mm thick in AISI 304 stainless steel with splashback 85 mm. Depth 70 cm. GN 1/1. With doors and drawers. Control panel with digital thermometer - thermostat.



(€

General information

Series	Universal
Supplier's model identifier	KUB13A
Category	counter cabinet
Туре	refrigerated counter
Line	catering - GN 1/1

Technical features

da rodda os	
Temperature ranges, °C	0/+10
Energy Efficiency Class	C
Energy consumption, kWh/24h	2,973
Energy consumption/year, kWh/a	1085
Method for energy consumption	EN 22041
Energy Efficiency Index	46,69
Net usable volume, lt	209
Volume, gross, lt	434
Climate class	5 (+40°C, 40% R.H.)
Heavy duty cabinets	This appliance is intended for use in ambient temperatures up to 40 $^{\circ}\text{C}$
Refrigerant/GWP	R290/3
Refrigerant charge, kg	0,07
LWA dB(A)	46
Cooling system	ventilated refrigeration system. U- flow air circulation to assure peak cooling unit reliability
Defrosting	automatic
Evaporation of condense drain	automatic

Refrigerated counter-GN1/1-AISI 304-Universal





KUB13A



Refr	rigeration power at -10°C W	465
Fred	quency/voltage	230V 1N~ / 50Hz
Elec	ctric power, kW	0,28
Constru	uction features	
Stru	ucture	one-piece structure with rounded internal corners
Exte	ernal material	AISI 304 stainless steel
Inte	rnal material	AISI 304 stainless steel
Inte	rnal bottom	with rounded corners
Insu	lation thickness, mm	60
Wor	rktop	worktop 60 mm thick in AISI 304 stainless steel (8/10mm), with soundproofing lining; with splashbac
Inte	rnal structure	AISI 304 stainless steel grid-supporting rack
Posi	itions (n.)/spaced, mm	11/40,5
Evap	porator	with an anti-corrosion treatment
Easy	ymaintenance	the cooling unit pulls out to simplify routine cleaning of the condenser
Feet	t	stainless steel AISI 304, adjustable in height
Heig	ght of feet, mm	140 ÷ 200
Equ	ipped with	doors and drawers
Drav	wers, type: 1/3	3
Control	l and functions	
Kinf	f of control	thermometer-thermostat
Disp	olay	digital
Alar	rms	optical
Standa	rd	
She	lf's dimensions, cm	32,5x53 GN1/1
Shel	lves and couple of guides	complete with 1 pair of AISI 304 stainless steel runners and 1 plastic-coated shelf GN1/1 per sectio
Dimens	sions and weights	
Pacl	king (LxDxH), cm	192x76x100
Dim	nensions (LxDxH), cm	185x70x98,5
		462
Gro	ss Weight (kg)	163