

KUJAM

Refrigerated counter-Depth 60cm-Universal

One-piece AISI 304 stainless steel body.Temperature ranges: 0/+10°C.Worktop 60 mm thick in AISI 304 stainless steel.Depth 60 cm.For shelves 32,5x46 cm.2 doors.Control panel with digital thermometer - thermostat.



CE

General information

zm	
ended for use in ambient tempera	tures up to 40 °C
ion system. U- flow air circulation t ty	o assure peak
ty	

ANGELO PO GRANDI CUCINE S.p.a. con socio unico Zona Industriale Campolungo, 79/81 - 63100 Ascoli Piceno – Italy www.sagispa.it | info@sagispa.it

Angelo Po S.p.a. reserves the right to make product changes and cannot be held responsible for omissions and/or errors. 1/2 PRINTED 18/05/2024 21:34:30



Refrigerated counter-Depth 60cm-Universal

KUJAM



Evaporation of condense drain	automatic
Refrigeration power at -10°C W	465
Frequency/voltage	230V 1N~ / 50Hz
Electric power, kW	0,28

Construction features

Structure	one-piece structure with rounded internal corners
External material	AISI 304 stainless steel
Internal material	AISI 304 stainless steel
Internal bottom	with rounded corners
Insulation thickness, mm	60
Worktop	worktop 60 mm thick in AISI 304 stainless steel (8/10mm), with soundproofing lining
Internal structure	AISI 304 stainless steel grid-supporting rack
Positions (n.)/spaced, mm	11/40,5
Evaporator	with an anti-corrosion treatment
Easymaintenance	the cooling unit pulls out to simplify routine cleaning of the condense
Feet	stainless steel AISI 304, adjustable in height
Height of feet, mm	140 ÷ 200
Equipped with	2 doors

Control and functions

	Kinf of control	thermometer-thermostat
	Display	digital
	Alarms	optical
ita	ndard	
	·····	

Sta

Key-lock	optional
Shelf's dimensions, cm	32,5x46
Shelves and couple of guides	complete with 1 pair of AISI 304 stainless steel runners and 1 plastic-coated shelf for section

Dimensions and weights

Packing (LxDxH), cm	146x66x90	(
Dimensions (LxDxH), cm	140x60x90				
Gross Weight (kg)	109				
Net Weight (kg)	99				

