

# FD15TPV



## Refrigerator glass door-GN2/1-AISI304-Freezy Prime

One-piece structure in AISI 304 stainless steel. Single compartment, GN2/1. 2 glass doors. Temperature ranges: 0/+10°C. Control panel with digital thermometer- thermostat. Fan-assisted refrigeration with external evaporator. Automatic defrosting. Lighting and key-operated lock.



### General information

|                             |                   |
|-----------------------------|-------------------|
| Supplier/producer 's name   | SAGI              |
| Series                      | Freezy Prime      |
| Supplier's model identifier | FD15TPV           |
| Category                    | display cabinet   |
| Type                        | refrigerator      |
| Line                        | catering - GN 2/1 |

### Technical features

|                                |                                 |
|--------------------------------|---------------------------------|
| Temperature ranges, °C         | 0/+10                           |
| Energy Efficiency Class        | E                               |
| Energy consumption, kWh/24h    | 4,5                             |
| Energy consumption/year, kWh/a | 1643                            |
| Method for energy consumption  | EN 22041                        |
| Energy Efficiency Index        | 76,74                           |
| Net usable volume, lt          | 932                             |
| Volume, gross, lt              | 1180                            |
| Climate class                  | 4 (+30°C, 55% R.H.)             |
| Refrigerant/GWP                | R290/3                          |
| Refrigerant charge, kg         | 0,115                           |
| LWA dB(A)                      | 51                              |
| Cooling system                 | ventilated refrigeration system |
| Defrosting                     | automatic by heating elements   |
| Evaporation of condense drain  | automatic                       |
| Refrigeration power at -10°C W | 601                             |

Refrigerator glass door-GN2/1-AISI304-Freezy Prime



# FD15TPV



|                    |                 |
|--------------------|-----------------|
| Frequency/voltage  | 230V 1N~ / 50Hz |
| Electric power, kW | 0,32            |

## Construction features

|                           |                                                                                          |
|---------------------------|------------------------------------------------------------------------------------------|
| Structure                 | one - piece structure with rounded internal corners                                      |
| External material         | AISI 304 stainless steel                                                                 |
| Internal material         | AISI 304 stainless steel (inner ceiling made of special anti-fingerprint steel)          |
| Insulation thickness, mm  | 75                                                                                       |
| Door                      | 2 glass doors                                                                            |
| Standard hinging door     | with self-closing device for openings inferior to 90°                                    |
| Internal structure        | AISI 304 stainless steel grid-supporting rack                                            |
| Positions (n.)/spaced, mm | 21/60                                                                                    |
| Evaporator                | positioned outside the compartment                                                       |
| Easymaintenance           | accessibility to all the functional and control components via a retractable front panel |
| Safety interlock switch   | yes, to stop internal fan                                                                |
| Feet                      | stainless steel AISI 304, adjustable in height                                           |
| Height of feet, mm        | 115 ÷ 165                                                                                |

## Control and functions

|                 |                        |
|-----------------|------------------------|
| Kinf of control | thermometer-thermostat |
| Display         | digital                |
| Alarms          | optical                |

## Standard

|                            |                                            |
|----------------------------|--------------------------------------------|
| Key-lock                   | yes                                        |
| Lighting                   | LED lighting                               |
| Couple of guides (n.)      | 6 pair of AISI 304 stainless steel runners |
| Shelves (n.)               | 6, plastic coated                          |
| Shelf's dimensions, cm     | 53x65 (GN 2/1)                             |
| Shelf loading capacity, kg | 48                                         |

## Dimensions and weights

|                        |              |
|------------------------|--------------|
| Packing (LxDxH), cm    | 154x85,5x207 |
| Dimensions (LxDxH), cm | 150x80x204   |
| Gross Weight (kg)      | 224          |
| Net Weight (kg)        | 204          |

## Notes

|       |                                                                                        |
|-------|----------------------------------------------------------------------------------------|
| Notes | Models ...PV, installation allowed to an altitude up to 800 metres above the sea level |
|-------|----------------------------------------------------------------------------------------|

Refrigerator glass door-GN2/1-AISI304-Freezy Prime

