
## **KAGL6BR**



One-piece structure in AISI 304 stainless steel. Rack bars in stainless steel AISI 304, 9 position step 150 mm pitch for 54 containers 36x16,5x12 cm. Refrigerator remote. Temperature ranges: -24/-12°C. Electronic circuit board with HACCP alarms and Hyper Cold function. Fan-assisted refrigeration with external evaporator. Automatic defrosting electric type. Lighting and key-operated lock.



# CE

#### **General information**

Supplier/producer 's name	SAGI
Series	lce Cream
Supplier's model identifier	KAGL6BR
Category	vertical cabinet
Туре	freezer for ice cream
Line	ice cream - n. 54 containers (36x16,5x12cm)
hnical features	
Temperature ranges, °C	-24/-12
Energy Efficiency Class	product are excluded from the European energy classification label according to EU Regulation 2015/1
Net usable volume, lt	538
Volume, gross, lt	682
Climate class	5 (+40°C, 40% R.H.)
Heavy duty cabinets	This appliance is intended for use in ambient temperatures up to 40 $^{\circ}$
Refrigerant/GWP	R452A/2141
LWA dB(A)	62
Cooling system	ventilated refrigeration system
Defrosting	automatic by heating elements
Evaporation of condense drain	automatic
Refrigeration power -23,3°C W	1054
Frequency/voltage	230V 1N~ / 50Hz
Electric power, kW	1,2

#### **Construction features**

ANGELO PO GRANDI CUCINE S.p.a. con socio unico Zona Industriale Campolungo, 79/81 - 63100 Ascoli Piceno – Italy www.sagispa.it | info@sagispa.it



**Refrigerator - Remote-AISI 304-Ice Cream** 



# KAGL6BR



Height of feet, mm	105 ÷ 155
Feet	stainless steel AISI 304, adjustable in height
Safety interlock switch	yes, to stop internal fan and switch on compartment light
Easymaintenance	accessibility to all the functional and control components via a retractable front panel
Evaporator	positioned outside the compartment
Internal structure	AISI 304 stainless steel racks with 9 positions spaced 150 mm apart for 54 containers 36x16,5x12 cm
Door handle	integrated full-height
Standard hinging door	on the right / reversible on the site with self-closing device for opening inferior to 90°
Door	1 door in AISI 304 stainless steel
Insulation thickness, mm	75
Internal bottom	diamond treated bottom
Internal material	AISI 304 stainless steel
External material	AISI 304 stainless steel
Structure	one-piece structure with rounded internal corners

Kinf of control	electronic pannel control board
Display	digital
Alarms	optical and acoustical
Functions/programs	Hyper Cold

#### Standard

Key-lock	yes
Lighting	yes
Couple of guides (n.)	6 pair of AISI 304 stainless steel runners
Shelves (n.)	6

### Dimensions and weights

Packing (LxDxH), cm	81x95x216
Dimensions (LxDxH), cm	75x90x204
Gross Weight (kg)	154
Net Weight (kg)	137

#### Notes

Notes

plus: thermostatic valve for a quick cooling - quick opening, thanks to the compensation valve

