

KC6A



Refrigerated display+14/+16°C Luxor New Style Slim

Display compartment in tempered glass throughout, black screen-silk printed. Glass door with invisible full-height handle. Lower structure in black color. Ventilated refrigeration with evaporator in the lower part of the structure. Setting of relative humidity through humidistat. Connection to APO.LINK portal for remote control of appliance through accessory (Industry 4.0)



General information

Supplier/producer 's name	SAGI
Series	Luxor New Style
Supplier's model identifier	KC6A
Category	upright refrigerated display units
Type	refrigerated display unit
Line	catering - pastry&bakery - ice-cream

Technical features

Temperature ranges, °C	+14+16
Relative humidity (%)	40÷44%
Energy Efficiency Class	product excluded from the European energy classification label according to EU Regulation 2019/2018
Volume, gross, lt	324
Climate class	4 (+30°C, 55% R.H.)
Refrigerant/GWP	R290/3
LWA dB(A)	65
Cooling system	ventilated refrigeration system
Evaporation of condense drain	automatic
Refrigeration power at -10°C W	362
Frequency/voltage	230V 1N~ / 50Hz
Electric power, kW	0,33

Construction features

Display compartment	completely in tempered glass with black screen-silk printed (RAL 9005), anti-condense heating elem.
---------------------	---

Refrigerated display+14/+16°C Luxor New Style Slim



KC6A



Lower structure	black color (RAL 9005)
LED lighting	high luminous intensity anti-glare, possibility to change the type of light*
Door	1 glass door
Standard hinging door	on the right / no-reversible on the site (contact the manufacturer for the left door)
Door handle	"invisible" full-height
Internal structure	AISI 304 stainless steel grid-supporting rack
Evaporator	positioned in the lower part of the structure
Easymaintenance	accessibility to all the functional and control components
Safety interlock switch	yes, to stop internal fan
Feet	nr.4 integrated wheels, hidden by the structure

Control and functions

Kinf of control	electronic control board with the communication port and signaling HACCP alarms
Display	digital with digit blue
Alarms	optical and acoustical
Functions/programs	PIR Sense proximity sensor, changes light intensity as customers approach

Standard

Shelf (n.)	5
Shelf's dimensions (cm)	49x47
Shelf loading capacity (kg)	12

Dimensions and weights

Packing (LxDxH), cm	74x76x202
Dimensions (LxDxH), cm	60x64,5x184
Gross Weight (kg)	198
Net Weight (kg)	178

Notes

Notes	- installation allowed to an altitude up to 800 meters above sea level *3000K-4000K-5000K-6000K
-------	--

Refrigerated display+14/+16°C Luxor New Style Slim

ANGELO PO GRANDI CUCINE S.p.a. con socio unico

Zona Industriale Campolungo, 79/81 - 63100 Ascoli Piceno - Italy

www.sagispa.it | info@sagispa.it

Angelo Po S.p.a. reserves the right to make product changes and cannot be held responsible for omissions and/or errors.

2/2 PRINTED 18/05/2024 22:59:28

