

KC8GSX



Refrigerated display unit +14/+16°C Luxor Classic

Display compartment in tempered glass throughout, externally screen-silk printed. Glass door with invisible full-height handle. Hinge positioned on the left side. LED lighting. Lower structure in special anti-fingerprint steel. Integrated wheels, hidden by the structure. Electronic p.c.b. HACCP alarms. Ventilated refrigeration through evaporator. Setting of relative humidity through humidistat.



General information

Supplier/producer 's name	SAGI
Series	Luxor Classic
Supplier's model identifier	KC8GSX
Category	upright refrigerated display units
Type	refrigerated display unit
Line	catering - pastry&bakery - ice-cream

Technical features

Temperature ranges, °C	+14/+16
Relative humidity (%)	40÷44%
Energy Efficiency Class	product excluded from the European energy classification label according to EU Regulation 2019/2018
Volume, gross, lt	457
Climate class	4 (+30°C, 55% R.H.)
Refrigerant/GWP	R290/3
LWA dB(A)	65
Cooling system	ventilated refrigeration system
Evaporation of condense drain	automatic
Refrigeration power at -10°C W	442
Frequency/voltage	230V 1N~ / 50Hz
Electric power, kW	0,3

Construction features

Display compartment	completely in tempered glass with grey screen-silk printed
Lower structure	special grey anti-fingerprint steel

Refrigerated display unit +14/+16°C Luxor Classic



LED lighting	high luminous intensity anti-glare LED bars, front panel on the back of the door
Door	1 glass door
Standard hinging door	on the left / no-reversible on the site
Door handle	"invisible" full-height
Internal structure	AISI 304 stainless steel grid-supporting rack
Evaporator	positioned in the lower part of the structure
Easymaintenance	accessibility to all the functional and control components - clip clap system
Safety interlock switch	yes, to stop internal fan
Feet	nr.4 integrated wheels, hidden by the structure

Control and functions

Kinf of control	electronic pannel control board
Display	digital
Alarms	optical and acoustical
Functions/programs	it is possible to lock keys

Standard

Shelf (n.)	5
Shelf's dimensions (cm)	70x47
Shelf loading capacity (kg)	12 (available the accessoire KSR25KGP: front bearing kit for shelves, to load up to 25 kg)

Dimensions and weights

Packing (LxDxH), cm	89x76x202
Dimensions (LxDxH), cm	80,5x64,5x184
Gross Weight (kg)	236
Net Weight (kg)	211

Notes

Notes	installation allowed to an altitude up to 800 meters above sea level (contact the company)
-------	--

Refrigerated display unit +14/+16°C Luxor Classic