

# NE70



## Refrigerator-press-formed sides GN2/1-Nex-to Plus

One-piece structure in AISI 304 stainless steel. The storage chamber consists of AISI 304 stainless steel press-formed internal sides, 20 positions spaced 55cm. Single compartment, GN2/1. 1 door. Temperature ranges: -2/+8°C. Control panel with digital thermometer- thermostat. Fan-assisted refrigeration with external evaporator. Automatic defrosting electric type. Lighting and key-operated lock.



CE

### General information

Supplier/producer 's name	SAGI
Series	Nex-to plus
Supplier's model identifier	NE70
Category	vertical cabinet
Type	refrigerator
Line	catering - GN 2/1

### Technical features

Temperature ranges, °C	-2/+8
Energy Efficiency Class	A
Energy consumption, kWh/24h	0,925
Energy consumption/year, kWh/a	338
Method for energy consumption	EN 22041
Energy Efficiency Index	24,9
Net usable volume, lt	455
Volume, gross, lt	521
Climate class	5 (+40°C, 40% R.H.)
Heavy duty cabinets	This appliance is intended for use in ambient temperatures up to 40 °C
Refrigerant/GWP	R600a/3
Refrigerant charge, kg	0,105
LWA dB(A)	38
Cooling system	ventilated refrigeration system
Defrosting	automatic by heating elements
Evaporation of condense drain	automatic

Refrigerator-press-formed sides GN2/1-Nex-to Plus

ANGELO PO GRANDI CUCINE S.p.a. con socio unico  
Zona Industriale Campolungo, 79/81 - 63100 Ascoli Piceno - Italy  
[www.sagispa.it](http://www.sagispa.it) | [info@sagispa.it](mailto:info@sagispa.it)

Angelo Po S.p.a. reserves the right to make product changes and cannot be held responsible for omissions and/or errors.

1/2 PRINTED 18/04/2024 16:53:23



# NE70



Refrigeration power at -10°C W	377
Frequency/voltage	230V 1N~ / 50Hz
Electric power, kW	0,23

## Construction features

Structure	one-piece structure with rounded internal corners
External material	AISI 304 stainless steel
Internal material	AISI 304 stainless steel
Internal bottom	diamond treated bottom
Insulation thickness, mm	75
Door	1 door in AISI 304 stainless steel
Standard hinging door	on the right / reversible on the site with self-closing device for openings inferior to 90°
Door handle	integrated full-height
Internal structure	with press-formed internal sides in AISI 304 stainless steel
Positions (n.)/spaced, mm	20/55
Evaporator	positioned outside the compartment
Safety interlock switch	yes, to stop internal fan and switch on compartment light
Feet	stainless steel AISI 304, adjustable in height
Height of feet, mm	115 ÷ 165

## Control and functions

Kinf of control	thermometer-thermostat RS485
Display	digital
Alarms	optical
Connectivity	with APOLINK accessory*, via Ethernet, for remote control – Industry 4.0

## Standard

Key-lock	yes
Lighting	yes
Shelves (n.)	3+1, plastic coated
Shelf's dimensions, cm	53x65 (GN 2/1)
Shelf loading capacity, kg	60

## Dimensions and weights

Packing (LxDxH), cm	79x85,5x218
Dimensions (LxDxH), cm	68,4x80x204
Gross Weight (kg)	121
Net Weight (kg)	105

## Notes

Notes	*only for models produced starting from 01/08/2024
-------	--

Refrigerator-press-formed sides GN2/1-Nex-to Plus

