## FD15BT

# JOGI

## Freezer-GN2/1-AISI 304-Freezy Prime

One-piece structure in AISI 304 stainless steel. Single compartment, GN2/1. 2 doors. Temperature ranges: -20/-10°C.Control panel with digital thermometer- thermostat. Fan-assisted refrigeration with external evaporator. Automatic defrosting. Lighting and key-operated lock.



( (

## **General information**

| Supplier/producer 's name   | SAGI              |
|-----------------------------|-------------------|
| Series                      | Freezy Prime      |
| Supplier's model identifier | FD15BT            |
| Category                    | vertical cabinet  |
| Туре                        | freezer           |
| Line                        | catering - GN 2/1 |

## **Technical features**

| Temperature ranges, °C         | -20/-10  |
|--------------------------------|--|
| Energy Efficiency Class        | F  |
| Energy consumption, kWh/24h    | 17,6   |
| Energy consumption/year, kWh/a | 6424   |
| Method for energy consumption  | EN 22041   |
| Energy Efficiency Index        | 94,55  |
| Net usable volume, lt          | 1080   |
| Volume, gross, lt              | 1180   |
| Climate class                  | 5 (+40°C, 40% R.H.)  |
| Heavy duty cabinets            | This appliance is intended for use in ambient temperatures up to 40 °C |
| Refrigerant/GWP                | R290/3   |
| Refrigerant charge, kg         | 0,14   |
| LWA dB(A)                      | 67   |
| Cooling system                 | ventilated refrigeration system  |
| Defrosting                     | automatic  |
| Evaporation of condense drain  | automatic  |
|                                |  |

ezer-GN2/1-AISI 304-Freezy Prime





## FD15BT

| Refrigeration power -23,3°C W | 844             |
|-------------------------------|-----------------|
| Frequency/voltage             | 230V 1N~ / 50Hz |
| Electric power, kW            | 0,92            |

## **Construction features**

| Structure                 | one - piece structure with rounded internal corners   |
|---------------------------|---|
| External material         | AISI 304 stainless steel  |
| Internal material         | AISI 304 stainless steel (door inner side and inner ceiling made of special anti-fingerprint steel) |
| Insulation thickness, mm  | 75  |
| Door                      | 2 doors in AISI 304 stainless steel   |
| Standard hinging door     | on the right/reversible on the site with self-closing device for openings inferior to $90^{\circ}$  |
| Door handle               | integrated full-height  |
| Internal structure        | AISI 304 stainless steel grid-supporting rack   |
| Positions (n.)/spaced, mm | 21/60   |
| Evaporator                | positioned outside the compartment  |
| Easymaintenance           | accessibility to all the functional and control components via a retractable front panel            |
| Safety interlock switch   | yes, to stop internal fan and switch on compartment light   |
| Feet                      | stainless steel AISI 304, adjustable in height  |
| Height of feet, mm        | 115 ÷ 165   |

#### **Control and functions**

| Kinf of control | thermometer-thermostat  |
|-----------------|-------------------------|
| Display         | digital                 |
| Alarms          | ontical and acquistical |

## Standard

| Key-lock                   | yes  |
|----------------------------|--|
| Lighting                   | yes  |
| Couple of guides (n.)      | 6 pair of AISI 304 stainless steel runners |
| Shelves (n.)               | 6, plastic coated                          |
| Shelf's dimensions, cm     | 53x65 (GN 2/1)                             |
| Shelf loading capacity, kg | 48   |

## **Dimensions and weights**

| Packing (LxDxH), cm    | 154x85,5x207 |
|------------------------|--------------|
| Dimensions (LxDxH), cm | 150x80x204   |
| Gross Weight (kg)      | 219          |
| Net Weight (kg)        | 199          |

