FD7BT



One-piece structure in AISI 304 stainless steel. Single compartment, GN2/1. 1 door. Temperature ranges: -20/-10°C.Control panel with digital thermometer- thermostat. Fan-assisted refrigeration with external evaporator.Automatic defrosting. Lighting and key-operated lock.



CE

General information

eneral information	
Supplier/producer 's name	SAGI
Series	Freezy Prime
Supplier's model identifier	FD7BT
Category	vertical cabinet
Туре	freezer
Line	catering - GN 2/1
echnical features	
	-20/-10
Energy Efficiency Class	D
Energy consumption, kWh/24h	6,5
Energy consumption/year, kWh/a	2373
Method for energy consumption	EN 22041
Energy Efficiency Index	62,96
Net usable volume, lt	466
Volume, gross, lt	590
Climate class	5 (+40°C, 40% R.H.)
Heavy duty cabinets	This appliance is intended for use in ambient temperatures up to 40 $^{\circ}\mathrm{C}$
Refrigerant/GWP	R290/3
Refrigerant charge, kg	0,1
LWA dB(A)	40
Cooling system	ventilated refrigeration system
Defrosting	automatic
Evaporation of condense drain	automatic

ANGELO PO GRANDI CUCINE S.p.a. con socio unico Zona Industriale Campolungo, 79/81 - 63100 Ascoli Piceno – Italy www.sagispa.it | info@sagispa.it

Angelo Po S.p.a. reserves the right to make product changes and cannot be held responsible for omissions and/or errors. 1/2 PRINTED 13/05/2024 20:06:23



Freezer-GN2/1-AISI 304-Freezy Prime



FD7BT



Refrigeration power -23,3°C W	610
Frequency/voltage	230V 1N~ / 50Hz
Electric power, kW	0,66

Construction features

Structure	one - piece structure with rounded internal corners
External material	AISI 304 stainless steel
Internal material	AISI 304 stainless steel (door inner side and inner ceiling made of special anti-fingerprint steel)
Insulation thickness, mm	75
Door	1 door in AISI 304 stainless steel
Standard hinging door	on the right/reversible on the site with self-closing device for openings inferior to 90°
Door handle	integrated full-height
Internal structure	AISI 304 stainless steel grid-supporting rack
Positions (n.)/spaced, mm	21/60
Evaporator	positioned outside the compartment
Easymaintenance	accessibility to all the functional and control components via a retractable front panel
Safety interlock switch	yes, to stop internal fan and switch on compartment light
Feet	stainless steel AISI 304, adjustable in height
Height of feet, mm	115 ÷ 165

Control and functions

Gross Weight (kg)

Net Weight (kg)

control and functions	
Kinf of control	thermometer-thermostat
Display	digital
Alarms	optical and acoustical
Standard	
Key-lock	yes
Lighting	yes
Couple of guides (n.)	3 pair of AISI 304 stainless steel runners
Shelves (n.)	3, plastic coated
Shelf's dimensions, cm	53x65 (GN 2/1)
Shelf loading capacity, kg	48
Dimensions and weights	
Packing (LxDxH), cm	79x85,5x213
Dimensions (LxDxH), cm	75x80x204

135

120

