HD15BT

106

Freezer-GN2/1-anti-fingerprint-Shine Prime

One-piece structure in special anti-fingerprint steel. Single compartment, GN2/1. 2 doors. Temperature ranges: -20/-10°C. Control panel with digital thermometer- thermostat. Fan-assisted refrigeration with external evaporator. Automatic defrosting. Lighting and key-operated lock.



((

General information

Supplier/producer 's name	SAGI
Series	Shine Prime
Supplier's model identifier	HD15BT
Category	vertical cabinet
Туре	freezer
Line	catering - GN 2/1

Technical features

Temperature ranges, °C	-20/-10
Energy Efficiency Class	F
Energy consumption, kWh/24h	17,6
Energy consumption/year, kWh/a	6424
Method for energy consumption	EN 22041
Energy Efficiency Index	94,55
Net usable volume, lt	1080
Volume, gross, lt	1180
Climate class	5 (+40°C, 40% R.H.)
Heavy duty cabinets	This appliance is intended for use in ambient temperatures up to 40 °C
Refrigerant/GWP	R290/3
Refrigerant charge, kg	0,14
LWA dB(A)	67
Cooling system	ventilated refrigeration system
Defrosting	automatic
Evaporation of condense drain	automatic

Freezer-GN2/1-anti-fingerprint-Shine Prime





HD15BT

Refrigeration power -23,3°C W	844
Frequency/voltage	230V 1N~ / 50Hz
Electric power, kW	0.92

_	-	. •		
Con	stru	ction	features	

Structure	one - piece structure with rounded internal corners
External material	special anti-fingerprint steel
Internal material	special anti-fingerprint steel
Insulation thickness, mm	75
Door	2 doors in special anti-fingerprint steel
Standard hinging door	on the right/reversible on the site with self-closing device for openings inferior to 90°
Door handle	integrated full-height
Internal structure	AISI 304 stainless steel grid-supporting rack
Positions (n.)/spaced, mm	21/60
Evaporator	positioned outside the compartment
Easymaintenance	accessibility to all the functional and control components via a retractable front panel
Safety interlock switch	yes, to stop internal fan and switch on compartment light
Feet	stainless steel AISI 304, adjustable in height
Height of feet, mm	115 ÷ 165

Control and functions

Kinf of control	thermometer-thermostat
Display	digital
Alarms	ontical and acoustical

Standard

Key-lock	yes
Lighting	yes
Couple of guides (n.)	24 plastic - coated hooks
Shelves (n.)	6, plastic coated
Shelf's dimensions, cm	53x65 (GN 2/1)
Shelf loading capacity, kg	35

Dimensions and weights

Packing (LxDxH), cm	154x85,5x207
Dimensions (LxDxH), cm	150x80x204
Gross Weight (kg)	219
Net Weight (kg)	199

