

# KBS11



## Refrigerated counter-EN60x40-AISI304-Pastry&Bakery

One-piece structure in AISI 304 stainless steel. Temperature ranges: -2/+8°C. Without worktop. Single compartment. EN 60x40cm. 1 door. Control panel digital thermometer - thermostat and communication port, possibility of adjusting the relative humidity to 75% or to 90%. Automatic defrosting.



### General information

Supplier/producer 's name	SAGI
Series	Pastry & Bakery
Supplier's model identifier	KBS11
Category	counter cabinet
Type	refrigerated counter
Line	pastry & bakery - EN 60x40

### Technical features

Temperature ranges, °C	-2/+8
Energy Efficiency Class	C
Energy consumption, kWh/24h	2,176
Energy consumption/year, kWh/a	794
Method for energy consumption	EN 22041
Energy Efficiency Index	37,88
Net usable volume, lt	120
Volume, gross, lt	193
Climate class	5 (+40°C, 40% R.H.)
Heavy duty cabinets	This appliance is intended for use in ambient temperatures up to 40 °C
Refrigerant/GWP	R290/3
Refrigerant charge, kg	0,07
LWA dB(A)	46
Cooling system	ventilated refrigeration system. U- flow air circulation to assure peak cooling unit reliability
Defrosting	automatic electric type

Refrigerated counter-EN60x40-AISI304-Pastry&Bakery



Evaporation of condense drain	automatic
Refrigeration power at -10°C W	465
Frequency/voltage	230V 1N~ / 50Hz
Electric power, kW	0,3

### Construction features

Structure	one-piece structure with rounded internal corners
External material	AISI 304 stainless steel
Internal material	AISI 304 stainless steel
Internal bottom	with rounded corners
Insulation thickness, mm	55
Worktop	without worktop
Internal structure	AISI 304 stainless steel grid-supporting rack
Positions (n.)/spaced, mm	7/75
Evaporator	with an anti-corrosion treatment
Easymaintenance	the cooling unit pulls out to simplify routine cleaning of the condenser
Feet	stainless steel AISI 304, adjustable in height
Height of feet, mm	140 ÷ 200
Equipped with	1 door

### Control and functions

Kinf of control	thermometer-thermostat, communication port, possibility adjusting relative humidity to 75% or to 90%
Display	digital
Alarms	optical

### Standard

Shelf's dimensions, cm	EN 60x40
Shelves and couple of guides	7 pair of AISI 304 stainless steel runners for section

### Dimensions and weights

Packing (LxDxH), cm	115x82x105
Dimensions (LxDxH), cm	110x72,5x83
Gross Weight (kg)	88
Net Weight (kg)	78