

KBS21A



Refrigerated counter-EN60x40-AISI304-Pastry&Bakery

One-piece structure in AISI 304 stainless steel. Temperature ranges: -2/+8°C. Worktop in AISI 304 stainless steel with splashback. EN 60x40cm. 3 doors. Control panel digital thermometer - thermostat and communication port, possibility of adjusting the relative humidity to 75% or to 90%.



General information

| | |
|-----------------------------|----------------------------|
| Supplier/producer 's name | SAGI |
| Series | Pastry & Bakery |
| Supplier's model identifier | KBS21A |
| Category | counter cabinet |
| Type | refrigerated counter |
| Line | pastry & bakery - EN 60x40 |

Technical features

| | |
|--------------------------------|--|
| Temperature ranges, °C | -2/+8 |
| Energy Efficiency Class | D |
| Energy consumption, kWh/24h | 3,749 |
| Energy consumption/year, kWh/a | 1368 |
| Method for energy consumption | EN 22041 |
| Energy Efficiency Index | 50,5 |
| Net usable volume, lt | 360 |
| Volume, gross, lt | 564 |
| Climate class | 5 (+40°C, 40% R.H.) |
| Heavy duty cabinets | This appliance is intended for use in ambient temperatures up to 40 °C |
| Refrigerant/GWP | R290/3 |
| Refrigerant charge, kg | 0,08 |
| LWA dB(A) | 50 |
| Cooling system | ventilated refrigeration system. U- flow air circulation to assure peak cooling unit reliability |
| Defrosting | automatic electric type |

Refrigerated counter-EN60x40-AISI304-Pastry&Bakery



KBS21A



| | |
|--------------------------------|-----------------|
| Evaporation of condense drain | automatic |
| Refrigeration power at -10°C W | 560 |
| Frequency/voltage | 230V 1N~ / 50Hz |
| Electric power, kW | 0,36 |

Construction features

| | |
|---------------------------|--|
| Structure | one-piece structure with rounded internal corners |
| External material | AISI 304 stainless steel |
| Internal material | AISI 304 stainless steel |
| Internal bottom | with rounded corners |
| Insulation thickness, mm | 55 |
| Worktop | worktop 50 mm thick in AISI 304 stainless steel, with soundproofing lining; with splashback(h=8,5cm) |
| Internal structure | AISI 304 stainless steel grid-supporting rack |
| Positions (n.)/spaced, mm | 7/75 |
| Evaporator | with an anti-corrosion treatment |
| Easymaintenance | the cooling unit pulls out to simplify routine cleaning of the condenser |
| Feet | stainless steel AISI 304, adjustable in height |
| Height of feet, mm | 140 ÷ 200 |
| Equipped with | 3 doors |

Control and functions

| | |
|-----------------|--|
| Kinf of control | thermometer-thermostat, communication port, possibility adjusting relative humidity to 75% or to 90% |
| Display | digital |
| Alarms | optical |

Standard

| | |
|------------------------------|--|
| Shelf's dimensions, cm | EN 60x40 |
| Shelves and couple of guides | 7 pair of AISI 304 stainless steel runners for section |

Dimensions and weights

| | |
|------------------------|-------------|
| Packing (LxDxH), cm | 215x82x115 |
| Dimensions (LxDxH), cm | 210x80x96,5 |
| Gross Weight (kg) | 175 |
| Net Weight (kg) | 160 |

Refrigerated counter-EN60x40-AISI304-Pastry&Bakery

ANGELO PO GRANDI CUCINE S.p.a. con socio unico

Zona Industriale Campolungo, 79/81 - 63100 Ascoli Piceno - Italy

www.sagispa.it | info@sagispa.it

Angelo Po S.p.a. reserves the right to make product changes and cannot be held responsible for omissions and/or errors.

2/2 PRINTED 06/05/2024 23:18:58

