KC6G

Refrigerated display +14/+16°C Luxor Classic Slim

Display compartment in tempered glass throughout, externally screen-silk printed. Glass door with invisible full-height handle. LED lighting. Lower structure in special anti-fingerprint steel. Integrated wheels, hidden by the structure. Electronic p.c.b. HACCP alarms. Ventilated refrigeration through evaporator. Setting of relative humidity through humidistat.



CE

General information

Series	Luxor Classic
Supplier's model identifier	KC6G
Category	upright refrigerated display units
Туре	refrigerated display unit
Line	catering - pastry&bakery - ice-cream
nnical features	
Temperature ranges, °C	+14/+16
Relative humidity (%)	40÷44%
Energy Efficiency Class	product excluded from the European energy classification label according to EU Regulation 2019/2018
Volume, gross, lt	324
Climate class	4 (+30°C, 55% R.H.)
Refrigerant/GWP	R290/3
LWA dB(A)	65
Cooling system	ventilated refrigeration system
Evaporation of condense drain	automatic
Refrigeration power at -10°C W	442
Frequency/voltage	230V 1N~ / 50Hz
Electric power, kW	0,27

Display compartment

Lower structure

special grey anti-fingerprint steel

completely in tempered glass with grey screen-silk printed

ANGELO PO GRANDI CUCINE S.p.a. con socio unico Zona Industriale Campolungo, 79/81 - 63100 Ascoli Piceno – Italy www.sagispa.it | info@sagispa.it

CSQ

Refrigerated display +14/+16°C Luxor Classic Slim

 \mathbf{O}

Angelo Po S.p.a. reserves the right to make product changes and cannot be held responsible for omissions and/or errors. 1/2 PRINTED 13/05/2024 07:29:14

KC6G



Feet	nr.4 integrated wheels, hidden by the structure
Safety interlock switch	yes, to stop internal fan
Easymaintenance	accessibility to all the functional and control components - clip clap system
Evaporator	positioned in the lower part of the structure
Internal structure	AISI 304 stainless steel grid-supporting rack
Door handle	"invisible" full-height
Standard hinging door	on the right / no-reversible on the site (contact the manufacturer fo the left door)
Door	1 glass door
LED lighting	high luminous intensity anti-glare LED bars, front panel on the back the door

Control and functions

	electronic pannel control board
Display	digital
Alarms	optical and acoustical
Functions/programs	it is possible to lock keys

Standard

Shelf (n.)	5
Shelf's dimensions (cm)	49x47
Shelf loading capacity (kg)	12 (available the accessoire KSR25KGP: front bearing kit for shelfs, to load up to 25 kg)

Dimensions and weights

Packing (LxDxH), cm	74x76x202
Dimensions (LxDxH), cm	60x64,5x184
Gross Weight (kg)	191
Net Weight (kg)	171

Notes

Notes

installation allowed to an altitude up to 800 meters above sea level (contact the company)

