JQG

KC8A

Refrigerated display unit+14/+16°C Luxor New Style

Display compartment in tempered glass throughout, black screen-silk printed. Glass door with invisible full-height handle. Lower structure in black color. Ventilated refrigeration with evaporator in the lower part of the structure. Setting of relative humidity through humidistat.Connection to APO.LINK portal for remote control of appliance through accessory (Industry 4.0)



CE

General information

Supplier/producer 's name	SAGI
Series	Luxor New Style
Supplier's model identifier	KC8A
Category	upright refrigerated display units
Туре	refrigerated display unit
Line	catering - pastry&bakery - ice-cream
nical features	
Temperature ranges, °C	+14+16
Relative humidity (%)	40÷44%
Energy Efficiency Class	product excluded from the European energy classification label according to EU Regulation 2019/2018
Volume, gross, lt	457
Climate class	4 (+30°C, 55% R.H.)
Refrigerant/GWP	R290/3
LWA dB(A)	65
Cooling system	ventilated refrigeration system
Evaporation of condense drain	automatic
Refrigeration power at -10°C W	425
Frequency/voltage	230V 1N~ / 50Hz
Electric power, kW	0,36

Construction features

Display compartment

completely in tempered glass with black screen-silk printed (RAL 9005), anti-condense heating elem.

ANGELO PO GRANDI CUCINE S.p.a. con socio unico Zona Industriale Campolungo, 79/81 - 63100 Ascoli Piceno – Italy www.sagispa.it | info@sagispa.it



Refrigerated display unit+14/+16°C Luxor New Style

Angelo Po S.p.a. reserves the right to make product changes and cannot be held responsible for omissions and/or errors 1/2 PRINTED 13/05/2024 09:12:24

KC8A



Lower structure	black color (RAL 9005)
LED lighting	high luminous intensity anti-glare, possibility to change the type of light*
Door	1 glass door
Standard hinging door	on the right / no-reversible on the site (contact the manufacturer fo the left door)
Door handle	"invisible" full-height
Internal structure	AISI 304 stainless steel grid-supporting rack
Evaporator	positioned in the lower part of the structure
Easymaintenance	accessibility to all the functional and control components
Safety interlock switch	yes, to stop internal fan
Feet	nr.4 integrated wheels, hidden by the structure

Control and functions

Kinf of control	electronic control board with the communication port and signaling HACCP alarms
Display	digital with digit blue
Connectivity	with APOLINK accessory for remote control – Industry 4.0
Alarms	optical and acoustical
Functions/programs	PIR Sense proximity sensor, changes light intensity as customers approach

Standard

Shelf (n.)	5
Shelf's dimensions (cm)	70x47
Shelf loading capacity (kg)	12

Dimensions and weights

89x76x202
80,5x64,5x184
247
222

Notes

Notes

- installation allowed to an altitude up to 800 meters above sea level *3000K-4000K-5000K-6000K

