KIGB2M



Refrigerated counter-GN1/1-AISI 304-I-green

One-piece AISI 304 stainless steel body. Temperature ranges: -2/+10°C. Worktop 60 mm thick in AISI 304 stainless steel. Depth 70 cm. GN 1/1. With doors and drawers. Control panel with digital thermometer - thermostat and communication port. Automatic defrosting electric type.



(E

General information

Series	l-green
Supplier's model identifier	KIGB2M
Category	counter cabinet
Туре	refrigerated counter
Line	catering - GN 1/1

Technical features

innear reacures	
Temperature ranges, °C	-2/+10
Energy Efficiency Class	В
Energy consumption, kWh/24h	1,89
Energy consumption/year, kWh/a	690
Method for energy consumption	EN 22041
Energy Efficiency Index	29,4
Net usable volume, lt	217
Volume, gross, lt	434
Climate class	5 (+40°C, 40% R.H.)
Heavy duty cabinets	This appliance is intended for use in ambient temperatures up to 40 $^{\circ}\text{C}$
Refrigerant/GWP	R290/3
Refrigerant charge, kg	0,07
LWA dB(A)	46
Cooling system	ventilated refrigeration system. U- flow air circulation to assure peak cooling unit reliability
Defrosting	automatic by heating elements
Evaporation of condense drain	automatic

Refrigerated counter-GN1/1-AISI 304-I-green





Refrigerated counter-GN1/1-AISI 304-I-green

KIGB2M



Refrigeration power at -	10°C W	406
Frequency/voltage		230V 1N~ / 50Hz
Electric power, kW		0,22
Construction features		
Structure		one-piece structure with rounded internal corners
External material		AISI 304 stainless steel
Internal material		AISI 304 stainless steel
Internal bottom		with rounded corners
Insulation thickness, mn	า	60
Worktop		worktop 60 mm thick in AISI 304 stainless steel (8/10mm), with soundproofing lining
Internal structure		AISI 304 stainless steel grid-supporting rack
Positions (n.)/spaced, mi	m	11/40,5
Evaporator		with an anti-corrosion treatment
Easymaintenance		the cooling unit pulls out to simplify routine cleaning of the condenser
Feet		stainless steel AISI 304, adjustable in height
Height of feet, mm		140 ÷ 200
Equipped with		door and drawers
Drawers, type: 1/2		2
Control and functions		
Kinf of control		digital thermometer/thermostat and communication port
Display		digital
Standard		
Shelf's dimensions, cm		32,5x53 GN1/1
Shelves and couple of gu	uides	complete with 1 pair of AISI 304 stainless steel runners and 1 plastic-coated shelf GN1/1 per sectio
Dimensions and weigh	nts	
Packing (LxDxH), cm		192x76x90
Dimensions (LxDxH), cm		185x70x90
Gross Weight (kg)		159
Net Weight (kg)		147

