

Refrigerated counter-GN1/1-AISI 304-Universal

One-piece AISI 304 stainless steel body.Temperature ranges:  
0/+10°C.Without top.Depth 70 cm.GN 1/1.2 doors.Control panel  
with digital thermometer - thermostat.



General information

|                             |                      |
|-----------------------------|----------------------|
| Supplier/producer 's name   | SAGI                 |
| Series                      | Universal            |
| Supplier's model identifier | KUA                  |
| Category                    | counter cabinet      |
| Type                        | refrigerated counter |
| Line                        | catering - GN 1/1    |

Technical features

|                                |                                                                                                  |
|--------------------------------|--------------------------------------------------------------------------------------------------|
| Temperature ranges, °C         | 0/+10                                                                                            |
| Energy Efficiency Class        | B                                                                                                |
| Energy consumption, kWh/24h    | 2,063                                                                                            |
| Energy consumption/year, kWh/a | 753                                                                                              |
| Method for energy consumption  | EN 22041                                                                                         |
| Energy Efficiency Index        | 34,21                                                                                            |
| Net usable volume, lt          | 161                                                                                              |
| Volume, gross, lt              | 290                                                                                              |
| Climate class                  | 5 (+40°C, 40% R.H.)                                                                              |
| Heavy duty cabinets            | This appliance is intended for use in ambient temperatures up to 40 °C                           |
| Refrigerant/GWP                | R290/3                                                                                           |
| Refrigerant charge, kg         | 0,07                                                                                             |
| LWA dB(A)                      | 46                                                                                               |
| Cooling system                 | ventilated refrigeration system. U- flow air circulation to assure peak cooling unit reliability |
| Defrosting                     | automatic                                                                                        |

Refrigerated counter-GN1/1-AISI 304-Universal

|                                |                 |
|--------------------------------|-----------------|
| Evaporation of condense drain  | automatic       |
| Refrigeration power at -10°C W | 465             |
| Frequency/voltage              | 230V 1N~ / 50Hz |
| Electric power, kW             | 0,28            |

### Construction features

|                           |                                                                          |
|---------------------------|--------------------------------------------------------------------------|
| Structure                 | one-piece structure with rounded internal corners                        |
| External material         | AISI 304 stainless steel                                                 |
| Internal material         | AISI 304 stainless steel                                                 |
| Internal bottom           | with rounded corners                                                     |
| Insulation thickness, mm  | 60                                                                       |
| Worktop                   | without worktop                                                          |
| Internal structure        | AISI 304 stainless steel grid-supporting rack                            |
| Positions (n.)/spaced, mm | 11/40,5                                                                  |
| Evaporator                | with an anti-corrosion treatment                                         |
| Easymaintenance           | the cooling unit pulls out to simplify routine cleaning of the condenser |
| Feet                      | stainless steel AISI 304, adjustable in height                           |
| Height of feet, mm        | 140 ÷ 200                                                                |
| Equipped with             | 2 doors                                                                  |

### Control and functions

|                 |                        |
|-----------------|------------------------|
| Kinf of control | thermometer-thermostat |
| Display         | digital                |
| Alarms          | optical                |

### Standard

|                              |                                                                                                      |
|------------------------------|------------------------------------------------------------------------------------------------------|
| Key-lock                     | optional                                                                                             |
| Shelf's dimensions, cm       | 32,5x53 GN1/1                                                                                        |
| Shelves and couple of guides | complete with 1 pair of AISI 304 stainless steel runners and 1 plastic-coated shelf GN1/1 per sectio |

### Dimensions and weights

|                        |           |
|------------------------|-----------|
| Packing (LxDxH), cm    | 146x76x90 |
| Dimensions (LxDxH), cm | 140x70x84 |
| Gross Weight (kg)      | 96        |
| Net Weight (kg)        | 86        |

Refrigerated counter-GN1/1-AISI 304-Universal