

## KUA11A

#### Refrigerated counter-GN1/1-AISI 304-Universal

One-piece AISI 304 stainless steel body.Temperature ranges: 0/+10°C.Worktop 60 mm thick in AISI 304 stainless steel with splashback 85 mm.Depth 70 cm.GN 1/1.With door and drawers.Control panel with digital thermometer - thermostat.



CE

#### **General information**

Series	Universal
Supplier's model identifier	KUA11A
Category	counter cabinet
Туре	refrigerated counter
Line	catering - GN 1/1
chnical features	
Temperature ranges, °C	0/+10
Energy Efficiency Class	C
Energy consumption, kWh/24h	2,268
Energy consumption/year, kWh/a	828
Method for energy consumption	EN 22041
Energy Efficiency Index	38,27
Net usable volume, lt	146
Volume, gross, lt	290
Climate class	5 (+40°C, 40% R.H.)
Heavy duty cabinets	This appliance is intended for use in ambient temperatures up to 40 $^{\circ}\mathrm{C}$
Refrigerant/GWP	R290/3
Refrigerant charge, kg	0,07
I WA dB(A)	46

LWA dB(A)46Cooling systemventilated refrigeration system. U- flow air circulation to assure peak<br/>cooling unit reliabilityDefrostingautomaticEvaporation of condense drainautomatic

ANGELO PO GRANDI CUCINE S.p.a. con socio unico Zona Industriale Campolungo, 79/81 - 63100 Ascoli Piceno – Italy www.sagispa.it | info@sagispa.it

ble for omissions and/or errors.



### **KUA11A**



Refrigeration power at -10°C W	465
Frequency/voltage	230V 1N~ / 50Hz
Electric power, kW	0,28

#### **Construction features**

Structure	one-piece structure with rounded internal corners
External material	AISI 304 stainless steel
Internal material	AISI 304 stainless steel
Internal bottom	with rounded corners
Insulation thickness, mm	60
Worktop	worktop 60 mm thick in AISI 304 stainless steel (8/10mm), with soundproofing lining; with splashbac
Internal structure	AISI 304 stainless steel grid-supporting rack
Positions (n.)/spaced, mm	11/40,5
Evaporator	with an anti-corrosion treatment
Easymaintenance	the cooling unit pulls out to simplify routine cleaning of the condens
Feet	stainless steel AISI 304, adjustable in height
Height of feet, mm	140 ÷ 200
Equipped with	door and drawers
Drawers, type: 1/3 + 2/3	1+1

Kinf of control	thermometer-thermostat	
Display	digital	
Alarms	optical	
Standard		
Key-lock	optional	
	22.5.52.014.4	

in	nensions and weights	
	Shelves and couple of guides	complete with 1 pair of AISI 304 stainless steel runners and 1 plastic-coated shelf GN1/1 per sectio
	Shelf's dimensions, cm	32,5x53 GN1/1

# Dir

Packing (LxDxH), cm	146x76x100
Dimensions (LxDxH), cm	140x70x98,5
Gross Weight (kg)	133
Net Weight (kg)	123

