

KUA13

Refrigerated counter-GN1/1-AISI 304-Universal

One-piece AISI 304 stainless steel body.Temperature ranges: 0/+10°C.Without top.Depth 70 cm.GN 1/1.With door and drawers.Control panel with digital thermometer - thermostat.



CE

General information

Series	Universal
Supplier's model identifier	KUA13
Category	counter cabinet
Туре	refrigerated counter
Line	catering - GN 1/1
echnical features	
Temperature ranges, °C	0/+10
Energy Efficiency Class	D
Energy consumption, kWh/24h	2,268
Energy consumption/year, kWh/a	828
Method for energy consumption	EN 22041
Energy Efficiency Index	39,06
Net usable volume, lt	129
Volume, gross, lt	290
Climate class	5 (+40°C, 40% R.H.)
Heavy duty cabinets	This appliance is intended for use in ambient temperatures up to 40 $^{\circ}$
Refrigerant/GWP	R290/3
Refrigerant charge, kg	0,07
LWA dB(A)	46
Cooling system	ventilated refrigeration system. U- flow air circulation to assure peak

Cooling system ventilated refrigeration system. U- flow air circulation to assure peak cooling unit reliability Defrosting automatic Evaporation of condense drain automatic

ANGELO PO GRANDI CUCINE S.p.a. con socio unico Zona Industriale Campolungo, 79/81 - 63100 Ascoli Piceno – Italy www.sagispa.it | info@sagispa.it



Refrigerated counter-GN1/1-AISI 304-Universal

KUA13



Refrigeration power at -10°C W	465
Frequency/voltage	230V 1N~ / 50Hz
Electric power, kW	0,28

Construction features

Drawers, type: 1/3	3
Equipped with	door and drawers
Height of feet, mm	140 ÷ 200
Feet	stainless steel AISI 304, adjustable in height
Easymaintenance	the cooling unit pulls out to simplify routine cleaning of the condens
Evaporator	with an anti-corrosion treatment
Positions (n.)/spaced, mm	11/40,5
Internal structure	AISI 304 stainless steel grid-supporting rack
Worktop	without worktop
Insulation thickness, mm	60
Internal bottom	with rounded corners
Internal material	AISI 304 stainless steel
External material	AISI 304 stainless steel
Structure	one-piece structure with rounded internal corners

Shelves and couple of guides	complete with 1 pair of AlSI 304 stainless steel runners and 1 plastic-coated shelf GN1/1 per sectio
Shelf's dimensions, cm	32,5x53 GN1/1
Key-lock	optional
andard	
Alarms	optical
Display	digital
Kinf of control	thermometer-thermostat

Di

-		
Packing (LxDxH), cm	146x76x90	
Dimensions (LxDxH), cm	140x70x84	
Gross Weight (kg)	111	
Net Weight (kg)	101	

