

# KUA4

### Refrigerated counter-GN1/1-AISI 304-Universal

One-piece AISI 304 stainless steel body.Temperature ranges: 0/+10°C.Without top.Depth 70 cm.GN 1/1.With 4 drawers.Control panel with digital thermometer - thermostat.



### **General information**

Energy Efficiency Index

Net usable volume, lt

Heavy duty cabinets

Refrigerant charge, kg

Evaporation of condense drain

Refrigerant/GWP

LWA dB(A)

Defrosting

Cooling system

Volume, gross, lt

Climate class

Series	Universal
Supplier's model identifier	KUA4
Category	counter cabinet
Туре	refrigerated counter
Line	catering - GN 1/1
nnical features	
Temperature ranges, °C	0/+10
Temperature ranges, °C	0/+10
Temperature ranges, °C Energy Efficiency Class	0/+10 D

41,77

114

290

R290/3

automatic

automatic

0,07

46

5 (+40°C, 40% R.H.)

cooling unit reliability

This appliance is intended for use in ambient temperatures up to 40 °C

ventilated refrigeration system. U- flow air circulation to assure peak

**ANGELO PO GRANDI CUCINE S.p.a. con socio unico** Zona Industriale Campolungo, 79/81 - 63100 Ascoli Piceno – Italy

www.sagispa.it | info@sagispa.it Angelo Po S.p.a. reserves the right to make product changes and cannot be held responsible for omissions and/or errors. 1/2 PRINTED 20/05/2024 02:44:13



## KUA4



Refrigeration power at -10°C W	465
Frequency/voltage	230V 1N~ / 50Hz
Electric power, kW	0,28

#### **Construction features**

Structure	one-piece structure with rounded internal corners
External material	AISI 304 stainless steel
Internal material	AISI 304 stainless steel
Internal bottom	with rounded corners
Insulation thickness, mm	60
Worktop	without worktop
Internal structure	AISI 304 stainless steel grid-supporting rack
Positions (n.)/spaced, mm	11/40,5
Evaporator	with an anti-corrosion treatment
Easymaintenance	the cooling unit pulls out to simplify routine cleaning of the condenser
Feet	stainless steel AISI 304, adjustable in height
Height of feet, mm	140 ÷ 200
Equipped with	drawers
Drawers, type: 1/2	4

### Cor

Kinf of control	thermometer-thermostat
Display	digital
Alarms	optical
Standard	
Standard Key-lock	optional

#### **Dimensions and weights**

-		
Packing (LxDxH), cm	146x76x90	
Dimensions (LxDxH), cm	140x70x84	
Gross Weight (kg)	120	
Net Weight (kg)	110	

plastic-coated shelf GN1/1 per sectio

