

# KUEA4M



## Refrigerated counter-GN1/1-antifingerprint-Twin

All-in-one structure in special anti-fingerprint steel.Temperature ranges: 0/+10°C.Worktop 60 mm thick in AISI 304 stainless steel.Depth 70 cm.GN 1/1. 4 drawers.Control panel with digital thermometer - thermostat.



### General information

|                             |                      |
|-----------------------------|----------------------|
| Supplier/producer 's name   | SAGI                 |
| Series                      | Twin                 |
| Supplier's model identifier | KUEA4M               |
| Category                    | counter cabinet      |
| Type                        | refrigerated counter |
| Line                        | catering - GN 1/1    |

### Technical features

|                                |                                                                                                  |
|--------------------------------|--------------------------------------------------------------------------------------------------|
| Temperature ranges, °C         | 0/+10                                                                                            |
| Energy Efficiency Class        | D                                                                                                |
| Energy consumption, kWh/24h    | 2,382                                                                                            |
| Energy consumption/year, kWh/a | 869                                                                                              |
| Method for energy consumption  | EN 22041                                                                                         |
| Energy Efficiency Index        | 41,77                                                                                            |
| Net usable volume, lt          | 114                                                                                              |
| Volume, gross, lt              | 290                                                                                              |
| Climate class                  | 5 (+40°C, 40% R.H.)                                                                              |
| Heavy duty cabinets            | This appliance is intended for use in ambient temperatures up to 40 °C                           |
| Refrigerant/GWP                | R290/3                                                                                           |
| Refrigerant charge, kg         | 0,07                                                                                             |
| LWA dB(A)                      | 46                                                                                               |
| Cooling system                 | ventilated refrigeration system. U- flow air circulation to assure peak cooling unit reliability |
| Defrosting                     | automatic                                                                                        |

Refrigerated counter-GN1/1-antifingerprint-Twin



# KUEA4M



|                                |                 |
|--------------------------------|-----------------|
| Evaporation of condense drain  | automatic       |
| Refrigeration power at -10°C W | 465             |
| Frequency/voltage              | 230V 1N~ / 50Hz |
| Electric power, kW             | 0,28            |

## Construction features

|                           |                                                                                     |
|---------------------------|-------------------------------------------------------------------------------------|
| Structure                 | one-piece structure with rounded internal corners                                   |
| External material         | special anti-fingerprint steel                                                      |
| Internal material         | special anti-fingerprint steel                                                      |
| Internal bottom           | with rounded corners                                                                |
| Insulation thickness, mm  | 60                                                                                  |
| Worktop                   | worktop 60 mm thick in AISI 304 stainless steel (8/10mm), with soundproofing lining |
| Internal structure        | AISI 304 stainless steel grid-supporting rack                                       |
| Positions (n.)/spaced, mm | 11/40,5                                                                             |
| Evaporator                | with an anti-corrosion treatment                                                    |
| Easymaintenance           | the cooling unit pulls out to simplify routine cleaning of the condenser            |
| Feet                      | stainless steel AISI 304, adjustable in height                                      |
| Height of feet, mm        | 140 ÷ 200                                                                           |
| Equipped with             | drawers                                                                             |
| Drawers, type: 1/2        | 4                                                                                   |

## Control and functions

|                 |                        |
|-----------------|------------------------|
| Kinf of control | thermometer-thermostat |
| Display         | digital                |
| Alarms          | optical                |

## Dimensions and weights

|                        |           |
|------------------------|-----------|
| Packing (LxDxH), cm    | 146x76x90 |
| Dimensions (LxDxH), cm | 140x70x90 |
| Gross Weight (kg)      | 141       |
| Net Weight (kg)        | 131       |

Refrigerated counter-GN1/1-antifingerprint-Twin

ANGELO PO GRANDI CUCINE S.p.a. con socio unico

Zona Industriale Campolungo, 79/81 - 63100 Ascoli Piceno – Italy

[www.sagispa.it](http://www.sagispa.it) | [info@sagispa.it](mailto:info@sagispa.it)

Angelo Po S.p.a. reserves the right to make product changes and cannot be held responsible for omissions and/or errors.

2/2 PRINTED 14/05/2024 13:16:28

