

KUEC4A



Refrigerated counter-GN1/1-antifingerprint-Twin

All-in-one structure in special anti-fingerprint steel.Temperature ranges: 0/+10°C.Worktop 60 mm thick in AISI 304 stainless steel with splashback 85 mm.Depth 70 cm.GN 1/1.With doors and drawers.Control panel with digital thermometer - thermostat.



General information

Supplier/producer 's name	SAGI
Series	Twin
Supplier's model identifier	KUEC4A
Category	counter cabinet
Type	refrigerated counter
Line	catering - GN 1/1

Technical features

Temperature ranges, °C	0/+10
Energy Efficiency Class	D
Energy consumption, kWh/24h	4,310
Energy consumption/year, kWh/a	1573
Method for energy consumption	EN 22041
Energy Efficiency Index	63,18
Net usable volume, lt	274
Volume, gross, lt	578
Climate class	5 (+40°C, 40% R.H.)
Heavy duty cabinets	This appliance is intended for use in ambient temperatures up to 40 °C
Refrigerant/GWP	R290/3
Refrigerant charge, kg	0,08
LWA dB(A)	50
Cooling system	ventilated refrigeration system. U- flow air circulation to assure peak cooling unit reliability
Defrosting	automatic

Refrigerated counter-GN1/1-antifingerprint-Twin



KUEC4A



Evaporation of condense drain	automatic
Refrigeration power at -10°C W	560
Frequency/voltage	230V 1N~ / 50Hz
Electric power, kW	0,32

Construction features

Structure	one-piece structure with rounded internal corners
External material	special anti-fingerprint steel
Internal material	special anti-fingerprint steel
Internal bottom	with rounded corners
Insulation thickness, mm	60
Worktop	worktop 60 mm thick in AISI 304 stainless steel (8/10mm), with soundproofing lining; with splashbac
Internal structure	AISI 304 stainless steel grid-supporting rack
Positions (n.)/spaced, mm	11/40,5
Evaporator	with an anti-corrosion treatment
Easymaintenance	the cooling unit pulls out to simplify routine cleaning of the condenser
Feet	stainless steel AISI 304, adjustable in height
Height of feet, mm	140 ÷ 200
Equipped with	doors and drawers
Drawers, type: 1/2	4

Control and functions

Kinf of control	thermometer-thermostat
Display	digital
Alarms	optical

Standard

Shelf's dimensions, cm	32,5x53 GN1/1
Shelves and couple of guides	complete with 1 pair of AISI 304 stainless steel runners and 1 plastic-coated shelf GN1/1 per sectio

Dimensions and weights

Packing (LxDxH), cm	235,5x75,5x100
Dimensions (LxDxH), cm	230x70x98,5
Gross Weight (kg)	197
Net Weight (kg)	182

Refrigerated counter-GN1/1-antifingerprint-Twin

