

FD15BR



Freezer-Remote-GN2/1-AISI 304-Freezy Prime

One-piece structure in AISI 304 stainless steel. Freezer remote. Single compartment, GN2/1. 2 doors. Temperature ranges: -20/-10°C. Control panel with digital thermometer- thermostat. Fan-assisted refrigeration with external evaporator. Automatic defrosting. Lighting and key-operated lock.



General information

Supplier/producer 's name	SAGI
Series	Freezy Plus
Supplier's model identifier	FD15BR
Category	vertical cabinet
Type	freezer
Line	catering - GN 2/1

Technical features

Temperature ranges, °C	-20/-10
Energy Efficiency Class	product are excluded from the European energy classification label according to EU Regulation 2015/1
Net usable volume, lt	1080
Volume, gross, lt	1180
Climate class	5 (+40°C, 40% R.H.)
Refrigerant/GWP	R452A/2141
LWA dB(A)	20
Cooling system	ventilated refrigeration system
Defrosting	automatic
Evaporation of condense drain	automatic
Refrigeration power -23,3°C W	1054
Frequency/voltage	220V/230V/240V 1N~ / 50+60 Hz
Electric power, kW	0,82

Construction features

Structure	one-piece structure with rounded internal corners
-----------	---

ANGELO PO GRANDI CUCINE S.p.a. con socio unico
Zona Industriale Campolungo, 79/81 - 63100 Ascoli Piceno - Italy
www.sagispa.it | info@sagispa.it

Angelo Po S.p.a. reserves the right to make product changes and cannot be held responsible for omissions and/or errors.

1/2 PRINTED 20/04/2024 00:25:49



Freezer-Remote-GN2/1-AISI 304-Freezy Prime

FD15BR



External material	AISI 304 stainless steel
Internal material	AISI 304 stainless steel (door inner side and inner ceiling made of special anti-fingerprint steel)
Internal bottom	with rounded corners
Insulation thickness, mm	75
Door	2 doors in AISI 304 stainless steel
Standard hinging door	on the right / reversible on the site with self-closing device for openings inferior to 90°
Door handle	integrated full-height
Internal structure	AISI 304 stainless steel grid-supporting rack
Positions (n.)/spaced, mm	21/60
Evaporator	with an anti-corrosion treatment
Easymaintenance	accessibility to all the functional and control components via a retractable front panel
Safety interlock switch	yes, to stop internal fan and switch on compartment light
Feet	stainless steel AISI 304, adjustable in height
Height of feet, mm	115 ÷ 165

Control and functions

Kinf of control	thermometer-thermostat
Display	digital
Alarms	optical

Standard

Key-lock	yes
Lighting	yes
Couple of guides (n.)	6 pair of AISI 304 stainless steel runners
Shelves (n.)	6, plastic coated
Shelf's dimensions, cm	53x65 (GN 2/1)
Shelf loading capacity, kg	48

Dimensions and weights

Packing (LxDxH), cm	154x85,5x207
Dimensions (LxDxH), cm	150x80x204
Gross Weight (kg)	185
Net Weight (kg)	165

Notes

Notes	absorption while defrosting
-------	-----------------------------

Freezer-Remote-GN2/1-AISI 304-Freezy Prime

