FD15BT

106

Freezer-GN2/1-AISI 304-Freezy Prime

One-piece structure in AISI 304 stainless steel. Single compartment, GN2/1. 2 doors. Temperature ranges: -20/-10°C.Control panel with digital thermometer- thermostat. Fan-assisted refrigeration with external evaporator. Automatic defrosting. Lighting and key-operated lock.



 ϵ

General information

Supplier/producer 's name	SAGI
Series	Freezy Prime
Supplier's model identifier	FD15BT
Category	vertical cabinet
Туре	freezer
Line	catering - GN 2/1

Technical features

Temperature ranges, °C	-20/-10
Energy Efficiency Class	F
Energy consumption, kWh/24h	17,6
Energy consumption/year, kWh/a	6424
Method for energy consumption	EN 22041
Energy Efficiency Index	94,55
Net usable volume, lt	1080
Volume, gross, lt	1180
Climate class	5 (+40°C, 40% R.H.)
Heavy duty cabinets	This appliance is intended for use in ambient temperatures up to 40 °C
Refrigerant/GWP	R290/3
Refrigerant charge, kg	0,14
LWA dB(A)	67
Cooling system	ventilated refrigeration system
Defrosting	automatic
Evaporation of condense drain	automatic

ezer-GN2/1-AISI 304-Freezy Prime





FD15BT

	VI

Refrigeration power -23,3°C W	844	
Frequency/voltage	230V 1N~ / 50Hz	
Electric power, kW	0,92	
struction features		
Structure	one - piece structure with rounded internal corners	
External material	AISI 304 stainless steel	
Internal material	AISI 304 stainless steel (door inner side and inner ceiling made of special anti-fingerprint steel)	
Insulation thickness, mm	75	
Door	2 doors in AISI 304 stainless steel	
Standard hinging door	on the right/reversible on the site with self-closing device for opening inferior to 90°	
Door handle	integrated full-height	
Internal structure	AISI 304 stainless steel grid-supporting rack	
Positions (n.)/spaced, mm	21/60	
Evaporator	positioned outside the compartment	
Easymaintenance	accessibility to all the functional and control components via a retractable front panel	
Safety interlock switch	yes, to stop internal fan and switch on compartment light	
Feet	stainless steel AISI 304, adjustable in height	
Height of feet, mm	115 ÷ 165	
trol and functions		
Kinf of control	thermometer-thermostat	
Display	digital	
Alarms	optical and acoustical	
ndard		
Key-lock	yes	
Lighting	yes	
Couple of guides (n.)	6 pair of AISI 304 stainless steel runners	
Shelves (n.)	6, plastic coated	
Shelf's dimensions, cm	53x65 (GN 2/1)	
Shelf loading capacity, kg	48	
ensions and weights		
Packing (LxDxH), cm	154x85,5x207	
Dimensions (LxDxH), cm	150x80x204	
Gross Weight (kg)	219	
Net Weight (kg)	199	