

FD6T



Refrigerator-Depth 70cm-AISI 304-Freezy Prime

One-piece structure in AISI 304 stainless steel. Single compartment, for grilles 55x53cm. 1 door. Temperature ranges: 0/+10°C. Control panel with digital thermometer- thermostat. Fan-assisted refrigeration with external evaporator. Automatic defrosting. Lighting and key-operated lock.



General information

| | |
|-----------------------------|-----------------|
| Supplier/producer 's name | SAGI |
| Series | Freezy Prime |
| Supplier's model identifier | FD6T |
| Category | storage cabinet |
| Type | refrigerator |
| Line | catering |

Technical features

| | |
|--------------------------------|--|
| Temperature ranges, °C | 0/+10 |
| Energy Efficiency Class | C |
| Energy consumption, kWh/24h | 1,625 |
| Energy consumption/year, kWh/a | 602 |
| Method for energy consumption | EN 22041 |
| Energy Efficiency Index | 47,94 |
| Net usable volume, lt | 394 |
| Volume, gross, lt | 520 |
| Climate class | 5 (+40°C, 40% R.H.) |
| Heavy duty cabinets | This appliance is intended for use in ambient temperatures up to 40 °C |
| Refrigerant/GWP | R290/3 |
| Refrigerant charge, kg | 0,08 |
| LWA dB(A) | 38 |
| Cooling system | ventilated refrigeration system |
| Defrosting | automatic |
| Evaporation of condense drain | automatic |

Refrigerator-Depth 70cm-AISI 304-Freezy Prime

ANGELO PO GRANDI CUCINE S.p.a. con socio unico
Zona Industriale Campolungo, 79/81 - 63100 Ascoli Piceno - Italy
www.sagispa.it | info@sagispa.it

Angelo Po S.p.a. reserves the right to make product changes and cannot be held responsible for omissions and/or errors.

1/2 PRINTED 23/04/2024 14:49:59



FD6T



| | |
|--------------------------------|-----------------|
| Refrigeration power at -10°C W | 406 |
| Frequency/voltage | 230V 1N~ / 50Hz |
| Electric power, kW | 0,25 |

Construction features

| | |
|---------------------------|---|
| Structure | one - piece structure with rounded internal corners |
| External material | AISI 304 stainless steel |
| Internal material | AISI 304 stainless steel (door inner side and inner ceiling made of special anti-fingerprint steel) |
| Insulation thickness, mm | 75 |
| Door | 1 door in AISI 304 stainless steel |
| Standard hinging door | on the right/reversible on the site with self-closing device for openings inferior to 90° |
| Door handle | integrated full-height |
| Internal structure | AISI 304 stainless steel grid-supporting rack |
| Positions (n.)/spaced, mm | 21/60 |
| Evaporator | positioned outside the compartment |
| Easymaintenance | accessibility to all the functional and control components via a retractable front panel |
| Safety interlock switch | yes, to stop internal fan and switch on compartment light |
| Feet | stainless steel AISI 304, adjustable in height |
| Height of feet, mm | 115 ÷ 165 |

Control and functions

| | |
|-----------------|------------------------|
| Kinf of control | thermometer-thermostat |
| Display | digital |
| Alarms | optical and acoustical |

Standard

| | |
|----------------------------|--|
| Key-lock | yes |
| Lighting | yes |
| Couple of guides (n.) | 3 pair of AISI 304 stainless steel runners |
| Shelves (n.) | 3, plastic coated |
| Shelf's dimensions, cm | 53x55 |
| Shelf loading capacity, kg | 40 |

Dimensions and weights

| | |
|------------------------|-----------|
| Packing (LxDxH), cm | 79x75x213 |
| Dimensions (LxDxH), cm | 75x70x204 |
| Gross Weight (kg) | 118 |
| Net Weight (kg) | 108 |

Refrigerator-Depth 70cm-AISI 304-Freezy Prime

