

FD7LB

Combi cabinet-GN2/1-AISI 304-Freezy Prime

One-piece structure in AISI 304 stainless steel. Two independent compartment, GN2/1. 2 doors. Temperature ranges: -2/+8°C ÷ -20/-10°C. Control panel with digital thermometer- thermostat. Fan-assisted refrigeration, evaporator inside the compartment. Automatic defrosting. Lighting and key-operated lock.



General information

| | |
|-----------------------------|----------------------------|
| Supplier/producer 's name | SAGI |
| Series | Freezy - Plus |
| Supplier's model identifier | FD7LB |
| Category | vertical cabinet |
| Type | combi refrigerator/freezer |
| Line | catering - GN 2/1 |

Technical features

| | |
|--------------------------------|--|
| Temperature ranges, °C | -2/+8 ÷ -20/-10 |
| Energy Efficiency Class | product are excluded from the European energy classification label according to EU Regulation 2015/1 |
| Net usable volume, lt | 289 |
| Volume, gross, lt | 535 |
| Climate class | 5 (+40°C, 40% R.H.) |
| Refrigerant/GWP | R290/3 |
| Refrigerant charge, kg | 0,06+0,1 |
| LWA dB(A) | 51 |
| Cooling system | ventilated refrigeration system |
| Defrosting | automatic by heating elements |
| Evaporation of condense drain | automatic |
| Refrigeration power at -10°C W | 345 |
| Refrigeration power -23,3°C W | 611 |
| Frequency/voltage | 230V 1N~ / 50Hz |
| Electric power, kW | 0,75 |

Combi cabinet-GN2/1-AISI 304-Freezy Prime



Construction features

| | |
|---------------------------|---|
| Structure | one - piece structure with rounded internal corners |
| External material | AISI 304 stainless steel |
| Internal material | AISI 304 stainless steel |
| Insulation thickness, mm | 75 |
| Door | 2x1/2 doors in AISI 304 stainless steel |
| Standard hinging door | on the right/reversible on the site with self-closing device for openings inferior to 90° |
| Door handle | integrated full-height |
| Internal structure | AISI 304 stainless steel grid-supporting rack |
| Positions (n.)/spaced, mm | 7+7/60 |
| Evaporator | with an anti-corrosion treatment |
| Easymaintenance | accessibility to all the functional and control components via a retractable front panel |
| Safety interlock switch | yes, to stop internal fan and switch on compartment light |
| Feet | stainless steel AISI 304, adjustable in height |
| Height of feet, mm | 105 ÷ 155 |

Control and functions

| | |
|-----------------|------------------------|
| Kinf of control | thermometer-thermostat |
| Display | digital |
| Alarms | optical and acoustical |

Standard

| | |
|----------------------------|--|
| Key-lock | yes |
| Lighting | yes |
| Couple of guides (n.) | 2+2 pair of AISI 304 stainless steel runners |
| Shelves (n.) | 2+2, plastic coated |
| Shelf's dimensions, cm | 53x65 (GN 2/1) |
| Shelf loading capacity, kg | 48 |

Dimensions and weights

| | |
|------------------------|-------------|
| Packing (LxDxH), cm | 79x85,5x207 |
| Dimensions (LxDxH), cm | 75x81,5x204 |
| Gross Weight (kg) | 177 |
| Net Weight (kg) | 162 |

Combi cabinet-GN2/1-AISI 304-Freezy Prime