

FD7LL



Combi refrigerator-GN2/1-AISI 304-Freezy Prime

One-piece structure in AISI 304 stainless steel. Two independent compartment, GN2/1. 2 doors. Temperature ranges: -2/+8°C + -2/+8°C. Control panel with touch thermometer- thermostat. Fan-assisted refrigeration, evaporator inside the compartment. Automatic defrosting. Lighting and key-operated lock.



General information

Supplier/producer 's name	SAGI
Series	Freezy - Prime
Supplier's model identifier	FD7LL
Category	storage cabinet
Type	refrigerator
Line	catering - GN 2/1

Technical features

Temperature ranges, °C	-2/+8
Energy Efficiency Class	E
Energy consumption, kWh/24h	2,4
Energy consumption/year, kWh/a	876
Method for energy consumption	EN 22041
Energy Efficiency Index	80,28
Net usable volume, lt	289
Volume, gross, lt	535
Climate class	5 (+40°C, 40% R.H.)
Heavy duty cabinets	This appliance is intended for use in ambient temperatures up to 40 °C
Refrigerant/GWP	R290/3
Refrigerant charge, kg	0,06+0,06
LWA dB(A)	48
Cooling system	ventilated refrigeration system
Defrosting	automatic
Evaporation of condense drain	automatic

Combi refrigerator-GN2/1-AISI 304-Freezy Prime

ANGELO PO GRANDI CUCINE S.p.a. con socio unico

Zona Industriale Campolungo, 79/81 - 63100 Ascoli Piceno - Italy

www.sagispa.it | info@sagispa.it

Angelo Po S.p.a. reserves the right to make product changes and cannot be held responsible for omissions and/or errors.

1/2 PRINTED 01/07/2025 22:25:42



Refrigeration power at -10°C W	345+345
Frequency/voltage	230V 1N~ / 50Hz
Electric power, kW	0,68

Construction features

Structure	one - piece structure with rounded internal corners
External material	AISI 304 stainless steel
Internal material	AISI 304 stainless steel
Insulation thickness, mm	75
Door	2 doors in AISI 304 stainless steel
Standard hinging door	on the right/reversible on the site with self-closing device for openings inferior to 90°
Door handle	integrated full-height
Internal structure	AISI 304 stainless steel grid-supporting rack
Positions (n.)/spaced, mm	7+7/60
Evaporator	with an anti-corrosion treatment
Easymaintenance	accessibility to all the functional and control components via a retractable front panel
Safety interlock switch	yes, to stop internal fan and switch on compartment light
Feet	stainless steel AISI 304, adjustable in height
Height of feet, mm	105 ÷ 155

Control and functions

Kinf of control	thermometer-thermostat
Display	touch
Alarms	optical and acoustical

Standard

Key-lock	yes
Lighting	yes
Couple of guides (n.)	2+2 pair of AISI 304 stainless steel runners
Shelves (n.)	2+2, plastic coated
Shelf's dimensions, cm	53x65 (GN 2/1)
Shelf loading capacity, kg	48

Dimensions and weights

Packing (LxDxH), cm	79x85,5x207
Dimensions (LxDxH), cm	75x81,5x204
Gross Weight (kg)	175
Net Weight (kg)	160