## **KC6GSX**

### Refrigerated display +14/+16°C Luxor Classic Slim

Display compartment in tempered glass throughout, externally screen-silk printed. Glass door with invisible full-height handle. Hinge positioned on the left side. LED lighting. Lower structure in special anti-fingerprint steel. Integrated wheels, hidden by the structure. Electronic p.c.b. HACCP alarms. Ventilated refrigeration through evaporator. Setting of relative humidity through humidistat.



# CE

### **General** information

Electric power, kW	0,27
Frequency/voltage	230V 1N~ / 50Hz
Refrigeration power at -10°C W	442
Evaporation of condense drain	automatic
Cooling system	ventilated refrigeration system
LWA dB(A)	65
Refrigerant/GWP	R290/3
Climate class	4 (+30°C, 55% R.H.)
Volume, gross, lt	324
Energy Efficiency Class	product excluded from the European energy classification label according to EU Regulation 2019/2018
Relative humidity (%)	40÷44%
Temperature ranges, °C	+14/+16
nical features	
Line	catering - pastry&bakery - ice-cream
Туре	refrigerated display unit
Category	upright refrigerated display units
Supplier's model identifier	KC6GSX
Series	Luxor Classic
Supplier/producer 's name	SAGI

Display compartment

#### Lower structure

special grey anti-fingerprint steel

completely in tempered glass with grey screen-silk printed

ANGELO PO GRANDI CUCINE S.p.a. con socio unico Zona Industriale Campolungo, 79/81 - 63100 Ascoli Piceno – Italy www.sagispa.it | info@sagispa.it

Refrigerated display +14/+16°C Luxor Classic Slim





## KC6GSX



LED lighting	high luminous intensity anti-glare LED bars, front panel on the back c the door
Door	1 glass door
Standard hinging door	on the left / no-reversible on the site
Door handle	"invisible" full-height
Internal structure	AISI 304 stainless steel grid-supporting rack
Evaporator	positioned in the lower part of the structure
Easymaintenance	accessibility to all the functional and control components - clip clap system
Safety interlock switch	yes, to stop internal fan
Feet	nr.4 integrated wheels, hidden by the structure

#### **Control and functions**

Kinf of control	electronic pannel control board
Display	digital
Alarms	optical and acoustical
Functions/programs	it is possible to lock keys

### Standard

Shelf (n.)	5
Shelf's dimensions (cm)	49x47
Shelf loading capacity (kg)	12 (available the accessoire KSR25KGP: front bearing kit for shelfs, to load up to 25 kg)

### **Dimensions and weights**

Packing (LxDxH), cm	74x76x202
Dimensions (LxDxH), cm	60x64,5x184
Gross Weight (kg)	191
Net Weight (kg)	171

### Notes

Notes

installation allowed to an altitude up to 800 meters above sea level (contact the company)

