



LUXOR BLACK

Upright refrigerated display units



Commercial Code	KC8QA
Temperature range	+14/ +16°C
Technical features	<ul style="list-style-type: none"> • Display compartment in tempered glass throughout, with black screen-silk printed glass • Lower structure in special anti-fingerprint steel black colour • One refrigerated room • Cooling unit at evaporation temperature -10 °C and condensation temperature 53,5°C rated at 668 W • Climate Class 4, room +30°C and 55% R.H. • Ventilated refrigeration obtained through the evaporator being positioned in the lower part of the structure • Relative humidity through humidistat: 40/44% • Automatic defrosting by air, every 6 hours, automatic evaporation of condense drain • Ventilated system on the back with the air circulation not directed straight at food • Refrigerant fluid: R452A • Black glass electronic panel control board with touch keys and HACCP alarms
Functional features	<ul style="list-style-type: none"> • Display shelves in tempered glass. possibility of loading up to 12 kg per shelf. On request available the accessoire KSR25KGP: front bearing kit for shelves, to load up to 25 kg • Easily removable magnetic gasket • Glass door with “invisible” full-height handle • Gross internal volume: 490 litri • High brightness LED bar lighting, front panel on the back of the door and on internal ceiling element in the display compartment • Installation allowed to an altitude up to 800 meters above sea level. For installation over 800, contact the company • Standard accessories: nr 5 display shelves in tempered glass with the back upright on AISI 304 stainless steel rack • Integrated wheels, hidden by the structure. (nr 4)
External size	80.5x64.5x184cm
Gross/Net weight	211/236 kg
Electrical power	0.57 kW Standard connection: V-Hz 230V 1N-/50Hz