

KD6GSX



Refrigerated display -22/+5°C Luxor Classic Slim

Display compartment in tempered glass throughout, externally screen-silk printed. Glass door with invisible full-height handle. Hinge positioned on the left side. LED lighting. Lower structure in special anti-fingerprint steel. Integrated wheels. Electronic p.c.b. HACCP alarms. Ventilated refrigeration, anti-condense heating elements, automatic defrosting by hot gas.



General information

| | |
|-----------------------------|--------------------------------------|
| Supplier/producer 's name | SAGI |
| Series | Luxor Classic |
| Supplier's model identifier | KD6GSX |
| Category | upright refrigerated display units |
| Type | refrigerated display unit |
| Line | catering - pastry&bakery - ice-cream |

Technical features

| | |
|--------------------------------|---------------------------------|
| Temperature ranges, °C | -22/+5 |
| Relative humidity (%) | 65÷40% |
| Energy Efficiency Class | D |
| Energy consumption/year, kWh/a | 6308 |
| Method for energy consumption | EN 23953 |
| Volume, gross, lt | 324 |
| Climate class | 4 (+30°C, 55% R.H.) |
| Refrigerant/GWP | R290/3 |
| LWA dB(A) | 70 |
| Cooling system | ventilated refrigeration system |
| Defrosting | automatic defrosting by hot gas |
| Evaporation of condense drain | automatic |
| Refrigeration power -23,3°C W | 931 |
| Frequency/voltage | 230V 1N~ / 50Hz |
| Electric power, kW | 1,25 |

Refrigerated display -22/+5°C Luxor Classic Slim



Construction features

| | |
|-------------------------|---|
| Display compartment | compartment in tempered glass throughout, grey screen-silk printed glass, anti-condense heating elem. |
| Lower structure | special grey anti-fingerprint steel |
| LED lighting | high luminous intensity anti-glare LED bars, front panel on the back of the door |
| Door | 1 glass door |
| Standard hinging door | on the left / no-reversible on the site |
| Door handle | "invisible" full-height |
| Internal structure | AISI 304 stainless steel grid-supporting rack |
| Evaporator | positioned on the top of the display compartment with AISI 304 stainless steel structure |
| Easymaintenance | accessibility to all the functional and control components - clip clap system |
| Safety interlock switch | yes, to stop internal fan |
| Feet | nr.4 integrated wheels, hidden by the structure |

Control and functions

| | |
|--------------------|---------------------------------|
| Kinf of control | electronic pannel control board |
| Display | digital |
| Alarms | optical and acoustical |
| Functions/programs | it is possible to lock keys |

Standard

| | |
|-----------------------------|--|
| Shelf (n.) | 5 |
| Shelf's dimensions (cm) | 49x47 |
| Shelf loading capacity (kg) | 12 (available the accessoire KSR25KGP: front bearing kit for shelves, to load up to 25 kg) |

Dimensions and weights

| | |
|------------------------|-------------|
| Packing (LxDxH), cm | 74x76x202 |
| Dimensions (LxDxH), cm | 60x64,5x184 |
| Gross Weight (kg) | 236 |
| Net Weight (kg) | 217 |

Notes

| | |
|-------|--|
| Notes | installation allowed to an altitude up to 800 meters above sea level (contact the company) |
|-------|--|