

KFSDR1N

PASTRY REFRIGERATOR 60x40 cm, ONE DOOR, POS.TEMP.

Exterior/interior in AISI304 18-10 s/steel. Ventil. cooling system with finned evaporator. Electronic thermometer/thermostat. Automatic defrosting electric type, automatic evaporation of condense drain AISI304 18-10 s/s handle and remov. shelf supports. Compartm. 60 x 40 suitable for remote cooling unit.



General information

Supplier/producer 's name	SAGI
Series	Pastry & Bakery
Supplier's model identifier	KFSDR1N
Category	vertical cabinet
Type	refrigerator
Line	pastry & bakery - EN 60x40

Technical features

Temperature ranges, °C	-2/+8
Energy Efficiency Class	product are excluded from the European energy classification label according to EU Regulation 2015/1
Method for energy consumption	EN 16825
Climate class	5 (+40°C, 40% R.H.)
Cooling system	ventilated refrigeration system
Defrosting	automatic by heating elements
Evaporation of condense drain	automatic
Frequency/voltage	230V 1N~ / 50Hz
Electric power, kW	0,4

Construction features

Structure	one-piece structure with rounded internal corners
External material	AISI 304 stainless steel
Internal material	AISI 304 stainless steel
Internal bottom	diamond treated bottom with drain hole
Insulation thickness, mm	75

ANGELO PO GRANDI CUCINE S.p.a. con socio unico
Zona Industriale Campolungo, 79/81 - 63100 Ascoli Piceno - Italy
www.sagispa.it | info@sagispa.it

Angelo Po S.p.a. reserves the right to make product changes and cannot be held responsible for omissions and/or errors.

1/2 PRINTED 10/05/2024 12:58:07



PASTRY REFRIGERATOR 60X40 cm, ONE DOOR, POS.TEMP.

KFSDR1N



Door	1 door in AISI 304 stainless steel
Standard hinging door	on the right / reversible on the site with self-closing device for openings inferior to 90°
Door handle	integrated full-height
Internal structure	AISI 304 stainless steel grid-supporting rack
Positions (n.)/spaced, mm	40/30
Evaporator	positioned outside the compartment
Easymaintenance	accessibility to all the functional and control components via a retractable front panel
Safety interlock switch	yes, to stop internal fan and switch on compartment light
Feet	stainless steel AISI 304, adjustable in height
Height of feet, mm	105 ÷ 155

Control and functions

Kinf of control	electronic pannel control board
Display	digital
Alarms	optical and acoustical
Functions/programs	Hyper Cold - Energy Saving - setting of the relative humidity to 75% or to 90%

Standard

Key-lock	yes
Lighting	yes
Couple of guides (n.)	20 pair of AISI 304 stainless steel runners

Dimensions and weights

Packing (LxDxH), cm	69x86,5x213
Dimensions (LxDxH), cm	62x80x204
Gross Weight (kg)	128
Net Weight (kg)	113

Notes

Notes	absorption while defrosting
-------	-----------------------------

PASTRY REFRIGERATOR 60x40 cm, ONE DOOR, POS.TEMP.

