## KFSDR2B

# **106**

### PASTRY FREEZER 60 x 80 cm, ONE DOOR

Exterior/interior AISI 304 18-10 st/steel. Ventil. cooling system with finned evaporator. Electronic

thermometer/thermostat.Automatic defrosting electric type, autom.evaporation of condense drain AISI304 18-10 s/s handle and remov.shelf supports. Compartm.60x80 cm suitable for remote cooling unit



 $\epsilon$ 

#### **General information**

Supplier/producer 's name	SAGI
Series	Pastry & Bakery
Supplier's model identifier	KFSDR2B
Category	vertical cabinet
Туре	freezer
Line	pastry & bakery - EN 60x80

#### **Technical features**

Temperature ranges, °C	-24/-12
Energy Efficiency Class	product are excluded from the European energy classification label according to EU Regulation 2015/1
Method for energy consumption	EN 16825
Climate class	5 (+40°C, 40% R.H.)
Cooling system	ventilated refrigeration system
Defrosting	automatic by heating elements
Evaporation of condense drain	automatic
Frequency/voltage	230V 1N~ / 50Hz
Electric power, kW	1,2

#### **Construction features**

Structure	one-piece structure with rounded internal corners
External material	AISI 304 stainless steel
Internal material	AISI 304 stainless steel
Internal bottom	diamond treated bottom
Insulation thickness, mm	75

I Net



PASTRY FREEZER 60 x 80 cm, ONE DOOR

## KFSDR2B



	Door	1 door in AISI 304 stainless steel
	Standard hinging door	on the right / reversible on the site with self-closing device for openings inferior to $90\ensuremath{^\circ}$
	Door handle	integrated full-height
	Internal structure	AISI 304 stainless steel grid-supporting rack
	Positions (n.)/spaced, mm	40/30
	Evaporator	positioned outside the compartment
	Easymaintenance	accessibility to all the functional and control components via a retractable front panel
	Safety interlock switch	yes, to stop internal fan and switch on compartment light
	Feet	stainless steel AISI 304, adjustable in height
	Height of feet, mm	105 ÷ 155
Co	entrol and functions	
	Kinf of control	electronic pannel control board
	Display	digital
	Alarms	optical and acoustical
	Functions/programs	Hyper Cold - Energy Saving - setting of the relative humidity to 75% or to 90%
St	andard	
	Key-lock	yes
	Lighting	yes
	Couple of guides (n.)	20 pair of AlSI 304 stainless steel runners
Di	mensions and weights	
	Packing (LxDxH), cm	89x106,5x213
	Dimensions (LxDxH), cm	82x100x204
	Gross Weight (kg)	173
	Net Weight (kg)	155

Notes absorption while defrosting