



# LUXOR BLACK

Upright refrigerated display units



<b>Commercial Code</b>	<b>KG8QA</b>
<b>Temperature range</b>	-25/ -15°C
<b>Technical features</b>	<ul style="list-style-type: none"> <li>• Display compartment in tempered glass throughout, with black screen-silk printed glass</li> <li>• Lower structure in special anti-fingerprint steel black colour</li> <li>• A single compartment temperature negative</li> <li>• Inner display unit with bottom condense drain hole</li> <li>• Cooling unit at evaporation temperature -23.3°C and condensation temperature 53,5°C rated at 1140 W</li> <li>• Climate Class 4, room +30°C and 55% R.H.</li> <li>• Static refrigeration obtained through the 5 static evaporating grids</li> <li>• Relative humidity: 75%</li> <li>• Manual stop-system for defrosting</li> <li>• Anti-condense heating elements</li> <li>• Refrigerant fluid: R452A</li> <li>• Black glass electronic panel control board with touch keys and HACCP alarms</li> </ul>
<b>Functional features</b>	<ul style="list-style-type: none"> <li>• Nr 5 evaporating grids + 1 display shelf</li> <li>• Easily removable magnetic gasket</li> <li>• Glass door with “invisible” full-height handle</li> <li>• Gross internal volume: 490 litri</li> <li>• High brightness LED bar lighting, front panel on the back of the door and on internal ceiling element in the display compartment</li> <li>• Installation allowed to an altitude up to 800 meters above sea level. For installation over 800, contact the company</li> <li>• Integrated wheels, hidden by the structure. (nr 4)</li> </ul>
<b>External size</b>	80.5x64.5x184cm
<b>Gross/Net weight</b>	217/242 kg
<b>Electrical power</b>	1,05 kW Standard connection: V-Hz 230V 1N-/50Hz