

# KIGC2M



## Refrigerated counter-GN1/1-AISI 304-I-green

One-piece AISI 304 stainless steel body. Temperature ranges: -2/+10°C. Worktop 60 mm thick in AISI 304 stainless steel. Depth 70 cm. GN 1/1. With doors and drawers. Control panel with digital thermometer - thermostat and communication port. Automatic defrosting electric type.



### General information

Series	I-green
Supplier's model identifier	KIGC2M
Category	counter cabinet
Type	refrigerated counter
Line	catering - GN 1/1

### Technical features

Temperature ranges, °C	-2/+10
Energy Efficiency Class	B
Energy consumption, kWh/24h	2,42
Energy consumption/year, kWh/a	885
Method for energy consumption	EN 22041
Energy Efficiency Index	34,7
Net usable volume, lt	298
Volume, gross, lt	578
Climate class	5 (+40°C, 40% R.H.)
Heavy duty cabinets	This appliance is intended for use in ambient temperatures up to 40 °C
Refrigerant/GWP	R290/3
Refrigerant charge, kg	0,08
LWA dB(A)	50
Cooling system	ventilated refrigeration system. U- flow air circulation to assure peak cooling unit reliability
Defrosting	automatic by heating elements
Evaporation of condense drain	automatic

Refrigerated counter-GN1/1-AISI 304-I-green



# KIGC2M



Refrigeration power at -10°C W	560
Frequency/voltage	230V 1N~ / 50Hz
Electric power, kW	0,28

## Construction features

Structure	one-piece structure with rounded internal corners
External material	AISI 304 stainless steel
Internal material	AISI 304 stainless steel
Internal bottom	with rounded corners
Insulation thickness, mm	60
Worktop	worktop 60 mm thick in AISI 304 stainless steel (8/10mm), with soundproofing lining
Internal structure	AISI 304 stainless steel grid-supporting rack
Positions (n.)/spaced, mm	11/40,5
Evaporator	with an anti-corrosion treatment
Easymaintenance	the cooling unit pulls out to simplify routine cleaning of the condenser
Feet	stainless steel AISI 304, adjustable in height
Height of feet, mm	140 ÷ 200
Equipped with	door and drawers
Drawers, type: 1/2	2

## Control and functions

Kinf of control	digital thermometer/thermostat and communication port
Display	digital

## Standard

Shelf's dimensions, cm	32,5x53 GN1/1
Shelves and couple of guides	complete with 1 pair of AISI 304 stainless steel runners and 1 plastic-coated shelf GN1/1 per sectio

## Dimensions and weights

Packing (LxDxH), cm	235,5x75,5x90
Dimensions (LxDxH), cm	230x70x90
Gross Weight (kg)	186
Net Weight (kg)	171

Refrigerated counter-GN1/1-AISI 304-I-green

