KUA4

JOGI

Refrigerated counter-GN1/1-AISI 304-Universal

One-piece AISI 304 stainless steel body. Temperature ranges: $0/+10^{\circ}$ C. Without top. Depth 70 cm. GN 1/1. With 4 drawers. Control panel with digital thermometer - thermostat.



 ϵ

General information

Series	Universal
Supplier's model identifier	KUA4
Category	counter cabinet
Туре	refrigerated counter
Line	catering - GN 1/1

Technical features

Temperature ranges, °C	0/+10
Energy Efficiency Class	D
Energy consumption, kWh/24h	2,382
Energy consumption/year, kWh/a	869
Method for energy consumption	EN 22041
Energy Efficiency Index	41,77
Net usable volume, It	114
Volume, gross, lt	290
Climate class	5 (+40°C, 40% R.H.)
Heavy duty cabinets	5 (+40°C, 40% R.H.) This appliance is intended for use in ambient temperatures up to 40 °C
Heavy duty cabinets	This appliance is intended for use in ambient temperatures up to 40 °C
Heavy duty cabinets Refrigerant/GWP	This appliance is intended for use in ambient temperatures up to 40 °C
Heavy duty cabinets Refrigerant/GWP Refrigerant charge, kg	This appliance is intended for use in ambient temperatures up to 40 °C R290/3 0,07
Heavy duty cabinets Refrigerant/GWP Refrigerant charge, kg LWA dB(A)	This appliance is intended for use in ambient temperatures up to 40 °C R290/3 0,07 46 ventilated refrigeration system. U- flow air circulation to assure peak

Refrigerated counter-GN1/1-AISI 304-Universal





Refrigeration power at -10°C W	465
Frequency/voltage	230V 1N~ / 50Hz
Electric power, kW	0,28

		_	_
Can	ctri	ıction	features

Structure	one-piece structure with rounded internal corners
External material	AISI 304 stainless steel
Internal material	AISI 304 stainless steel
Internal bottom	with rounded corners
Insulation thickness, mm	60
Worktop	without worktop
Internal structure	AISI 304 stainless steel grid-supporting rack
Positions (n.)/spaced, mm	11/40,5
Evaporator	with an anti-corrosion treatment
Easymaintenance	the cooling unit pulls out to simplify routine cleaning of the condenser
Feet	stainless steel AISI 304, adjustable in height
Height of feet, mm	140 ÷ 200
Equipped with	drawers
Drawers, type: 1/2	4

Control and functions

Kinf of control	thermometer-thermostat
Display	digital
Alarms	optical

Standard

Key-lock	optional
Shelves and couple of guides	complete with 1 pair of AISI 304 stainless steel runners and 1
	plastic-coated shelf GN1/1 per sectio

Dimensions and weights

Packing (LxDxH), cm	146x76x90
Dimensions (LxDxH), cm	140x70x84
Gross Weight (kg)	120
Net Weight (kg)	110

