

KUB2A

Refrigerated counter-GN1/1-AISI 304-Universal

One-piece AISI 304 stainless steel body.Temperature ranges: 0/+10°C.Worktop 60 mm thick in AISI 304 stainless steel with splashback 85 mm.Depth 70 cm.GN 1/1.With doors and drawers.Control panel with digital thermometer - thermostat.



CE

General information

| Supplier/producer 's name | SAGI |
|--------------------------------|--|
| Series | Universal |
| Supplier's model identifier | KUB2A |
| Category | counter cabinet |
| Туре | refrigerated counter |
| Line | catering - GN 1/1 |
| chnical features | |
| Temperature ranges, °C | 0/+10 |
| Energy Efficiency Class | C |
| Energy consumption, kWh/24h | 2,973 |
| Energy consumption/year, kWh/a | 1085 |
| Method for energy consumption | EN 22041 |
| Energy Efficiency Index | 46,29 |
| Net usable volume, lt | 217 |
| Volume, gross, lt | 434 |
| Climate class | 5 (+40°C, 40% R.H.) |
| Heavy duty cabinets | This appliance is intended for use in ambient temperatures up to 40 ° |
| Refrigerant/GWP | R290/3 |
| Refrigerant charge, kg | 0,07 |
| LWA dB(A) | 46 |
| Cooling system | ventilated refrigeration system. U- flow air circulation to assure peak cooling unit reliability |
| | |

ANGELO PO GRANDI CUCINE S.p.a. con socio unico Zona Industriale Campolungo, 79/81 - 63100 Ascoli Piceno – Italy www.sagispa.it | info@sagispa.it Angelo Po S.p.a. reserves the right to make product changes and cam



Refrigerated counter-GN1/1-AISI 304-Universal

Angelo Po S.p.a. reserves the right to make product changes and cannot be held responsible for omissions and/or errors. 1/2 PRINTED 25/04/2024 06:53:56

KUB2A



| Evaporation of condense drain | automatic |
|--------------------------------|-----------------|
| Refrigeration power at -10°C W | 465 |
| Frequency/voltage | 230V 1N~ / 50Hz |
| Electric power, kW | 0,28 |

Construction features

| Structure | one-piece structure with rounded internal corners |
|---------------------------|---|
| External material | AISI 304 stainless steel |
| Internal material | AISI 304 stainless steel |
| Internal bottom | with rounded corners |
| Insulation thickness, mm | 60 |
| Worktop | worktop 60 mm thick in AISI 304 stainless steel (8/10mm), with soundproofing lining; with splashbac |
| Internal structure | AISI 304 stainless steel grid-supporting rack |
| Positions (n.)/spaced, mm | 11/40,5 |
| Evaporator | with an anti-corrosion treatment |
| Easymaintenance | the cooling unit pulls out to simplify routine cleaning of the condense |
| Feet | stainless steel AISI 304, adjustable in height |
| Height of feet, mm | 140 ÷ 200 |
| Equipped with | doors and drawers |
| Drawers, type: 1/2 | 2 |

Control and functions

Gross Weight (kg)

Net Weight (kg)

| Kinf of control | thermometer-thermostat |
|------------------------------|--|
| Display | digital |
| Alarms | optical |
| Standard | |
| Key-lock | optional |
| Shelf's dimensions, cm | 32,5x53 GN1/1 |
| Shelves and couple of guides | complete with 1 pair of AISI 304 stainless steel runners and 1 plastic-coated shelf GN1/1 per sectio |
| Dimensions and weights | |
| Packing (LxDxH), cm | 192x76x100 |
| Dimensions (LxDxH), cm | 185x70x98,5 |
| | |

160

148

