KUB6

JOGI

Refrigerated counter-GN1/1-AISI 304-Universal

One-piece AISI 304 stainless steel body. Temperature ranges: $0/+10^{\circ}$ C. Without top. Depth 70 cm. GN 1/1. With 6 drawers. Control panel with digital thermometer - thermostat.



 ϵ

General information

Supplier/producer 's name	SAGI
Series	Universal
Supplier's model identifier	KUB6
Category	counter cabinet
Туре	refrigerated counter
Line	catering - GN 1/1

Technical features

Temperature ranges, °C	0/+10
Energy Efficiency Class	D
Energy consumption, kWh/24h	3,598
Energy consumption/year, kWh/a	1313
Method for energy consumption	EN 22041
Energy Efficiency Index	58,97
Net usable volume, It	171
Volume, gross, lt	434
Climate class	5 (+40°C, 40% R.H.)
Heavy duty cabinets	This appliance is intended for use in ambient temperatures up to 40 °C
Refrigerant/GWP	R290/3
Refrigerant charge, kg	0,07
LWA dB(A)	46
Cooling system	ventilated refrigeration system. U- flow air circulation to assure peak cooling unit reliability
Defrosting	automatic

Refrigerated counter-GN1/1-AISI 304-Universal





Refrigerated counter-GN1/1-AISI 304-Universal

KUB6



Evaporation of condense drain	automatic
Refrigeration power at -10°C W	465
Frequency/voltage	230V 1N~ / 50Hz
Electric power, kW	0,28
nstruction features	
Structure	one-piece structure with rounded internal corners
External material	AISI 304 stainless steel
Internal material	AISI 304 stainless steel
Internal bottom	with rounded corners
Insulation thickness, mm	60
Worktop	without worktop
Internal structure	AISI 304 stainless steel grid-supporting rack
Positions (n.)/spaced, mm	11/40,5
Evaporator	with an anti-corrosion treatment
Easymaintenance	the cooling unit pulls out to simplify routine cleaning of the condenser
Feet	stainless steel AISI 304, adjustable in height
Height of feet, mm	140 ÷ 200
Equipped with	drawers
Drawers, type: 1/2	6
trol and functions	
Kinf of control	thermometer-thermostat
Display	digital
Alarms	optical
ndard	
Key-lock	optional
Shelves and couple of guides	complete with 1 pair of AISI 304 stainless steel runners and 1 plastic-coated shelf GN1/1 per sectio
mensions and weights	
Packing (LxDxH), cm	192x76x92
Dimensions (LxDxH), cm	185x70x84

Packing (LxDxH), cm	192x76x92
Dimensions (LxDxH), cm	185x70x84
Gross Weight (kg)	155
Net Weight (kg)	143



