

# KUEB4A



## Refrigerated counter-GN1/1-antifingerprint-Twin

All-in-one structure in special anti-fingerprint steel.Temperature ranges: 0/+10°C.Worktop 60 mm thick in AISI 304 stainless steel with splashback 85 mm.Depth 70 cm.GN 1/1.With door and drawers.Control panel with digital thermometer - thermostat.



### General information

|                             |                      |
|-----------------------------|----------------------|
| Supplier/producer 's name   | SAGI                 |
| Series                      | Twin                 |
| Supplier's model identifier | KUEB4A               |
| Category                    | counter cabinet      |
| Type                        | refrigerated counter |
| Line                        | catering - GN 1/1    |

### Technical features

|                                |  |
|--------------------------------|--|
| Temperature ranges, °C         | 0/+10  |
| Energy Efficiency Class        | D  |
| Energy consumption, kWh/24h    | 3,271  |
| Energy consumption/year, kWh/a | 1194   |
| Method for energy consumption  | EN 22041   |
| Energy Efficiency Index        | 52,23  |
| Net usable volume, lt          | 194  |
| Volume, gross, lt              | 434  |
| Climate class                  | 5 (+40°C, 40% R.H.)  |
| Heavy duty cabinets            | This appliance is intended for use in ambient temperatures up to 40 °C                           |
| Refrigerant/GWP                | R290/3   |
| Refrigerant charge, kg         | 0,07   |
| LWA dB(A)                      | 46   |
| Cooling system                 | ventilated refrigeration system. U- flow air circulation to assure peak cooling unit reliability |
| Defrosting                     | automatic  |

Refrigerated counter-GN1/1-antifingerprint-Twin



# KUEB4A



|                                |                 |
|--------------------------------|-----------------|
| Evaporation of condense drain  | automatic       |
| Refrigeration power at -10°C W | 465             |
| Frequency/voltage              | 230V 1N~ / 50Hz |
| Electric power, kW             | 0,28            |

## Construction features

|                           |   |
|---------------------------|---|
| Structure                 | one-piece structure with rounded internal corners   |
| External material         | special anti-fingerprint steel  |
| Internal material         | special anti-fingerprint steel  |
| Internal bottom           | with rounded corners  |
| Insulation thickness, mm  | 60  |
| Worktop                   | worktop 60 mm thick in AISI 304 stainless steel (8/10mm), with soundproofing lining; with splashbac |
| Internal structure        | AISI 304 stainless steel grid-supporting rack   |
| Positions (n.)/spaced, mm | 11/40,5   |
| Evaporator                | with an anti-corrosion treatment  |
| Easymaintenance           | the cooling unit pulls out to simplify routine cleaning of the condenser                            |
| Feet                      | stainless steel AISI 304, adjustable in height  |
| Height of feet, mm        | 140 ÷ 200   |
| Equipped with             | door and drawers  |
| Drawers, type: 1/2        | 4   |

## Control and functions

|                 |                        |
|-----------------|------------------------|
| Kinf of control | thermometer-thermostat |
| Display         | digital                |
| Alarms          | optical and acoustical |

## Standard

|                              |  |
|------------------------------|--|
| Shelf's dimensions, cm       | 32,5x53 GN1/1  |
| Shelves and couple of guides | complete with 1 pair of AISI 304 stainless steel runners and 1 plastic-coated shelf GN1/1 per sectio |

## Dimensions and weights

|                        |             |
|------------------------|-------------|
| Packing (LxDxH), cm    | 192x76x100  |
| Dimensions (LxDxH), cm | 185x70x98,5 |
| Gross Weight (kg)      | 172         |
| Net Weight (kg)        | 160         |

Refrigerated counter-GN1/1-antifingerprint-Twin

