KUEBA

JOGI

Refrigerated counter-GN1/1-antifingerprint-Twin

All-in-one structure in special anti-fingerprint steel. Temperature ranges: 0/+10°C. Worktop 60 mm thick in AISI 304 stainless steel with splashback 85 mm. Depth 70 cm. GN 1/1.3 doors. Control panel with digital thermometer - thermostat.



 ϵ

General information

Supplier/producer 's name	SAGI
Series	Twin
Supplier's model identifier	KUEBA
Category	counter cabinet
Туре	refrigerated counter
Line	catering - GN 1/1

Technical features

Temperature ranges, °C	0/+10
Energy Efficiency Class	С
Energy consumption, kWh/24h	2,704
Energy consumption/year, kWh/a	987
Method for energy consumption	EN 22041
Energy Efficiency Index	41,02
Net usable volume, It	241
Volume, gross, lt	434
Climate class	5 (+40°C, 40% R.H.)
Heavy duty cabinets	This appliance is intended for use in ambient temperatures up to 40 °C
Refrigerant/GWP	R290/3
Refrigerant charge, kg	0,07
LWA dB(A)	46
Cooling system	ventilated refrigeration system. U- flow air circulation to assure peak cooling unit reliability
Defrosting	automatic

Refrigerated counter-GN1/1-antifingerprint-Twin





Refrigerated counter-GN1/1-antifingerprint-Twin

KUEBA



NU	FRA	
E	Evaporation of condense drain	automatic
F	Refrigeration power at -10°C W	465
F	Frequency/voltage	230V 1N~ / 50Hz
E	Electric power, kW	0,28
Cons	truction features	
9	Structure	one-piece structure with rounded internal corners
E	External material	special anti-fingerprint steel
Ī	nternal material	special anti-fingerprint steel
Ī	nternal bottom	with rounded corners
Ī	nsulation thickness, mm	60
\	Worktop	worktop 60 mm thick in AISI 304 stainless steel (8/10mm), with soundproofing lining; with splashbac
I	nternal structure	AISI 304 stainless steel grid-supporting rack
F	Positions (n.)/spaced, mm	11/40,5
E	Evaporator	with an anti-corrosion treatment
- E	Easymaintenance	the cooling unit pulls out to simplify routine cleaning of the condenser
F		stainless steel AISI 304, adjustable in height
ŀ	Height of feet, mm	140 ÷ 200
E	Equipped with	3 doors
Cont	rol and functions	
ŀ	Kinf of control	thermometer-thermostat
[Display	digital
Ā	Alarms	optical
Stan	dard	
ŀ	Key-lock	optional
9	Shelf's dimensions, cm	32,5x53 GN1/1
9	Shelves and couple of guides	complete with 1 pair of AISI 304 stainless steel runners and 1 plastic-coated shelf GN1/1 per sectio
Dime	ensions and weights	
F	Packing (LxDxH), cm	192x76x100
-	Dimensions (LxDxH), cm	185x70x98,5

148

136



Gross Weight (kg)

Net Weight (kg)