# **KUEBA**

# JOGI

# Refrigerated counter-GN1/1-antifingerprint-Twin

All-in-one structure in special anti-fingerprint steel. Temperature ranges: 0/+10°C. Worktop 60 mm thick in AISI 304 stainless steel with splashback 85 mm. Depth 70 cm. GN 1/1.3 doors. Control panel with digital thermometer - thermostat.



 $\epsilon$ 

### **General information**

Supplier/producer 's name	SAGI
Series	Twin
Supplier's model identifier	KUEBA
Category	counter cabinet
Туре	refrigerated counter
Line	catering - GN 1/1

### **Technical features**

Temperature ranges, °C	0/+10
Energy Efficiency Class	С
Energy consumption, kWh/24h	2,704
Energy consumption/year, kWh/a	987
Method for energy consumption	EN 22041
Energy Efficiency Index	41,02
Net usable volume, It	241
Volume, gross, lt	434
Climate class	5 (+40°C, 40% R.H.)
Heavy duty cabinets	This appliance is intended for use in ambient temperatures up to 40 $^{\circ}\text{C}$
Refrigerant/GWP	R290/3
Refrigerant charge, kg	0,07
LWA dB(A)	46
Cooling system	ventilated refrigeration system. U- flow air circulation to assure peak cooling unit reliability
Defrosting	automatic

Refrigerated counter-GN1/1-antifingerprint-Twin





# Refrigerated counter-GN1/1-antifingerprint-Twin

# **KUEB**



Evaporation of condense drain	automatic
Refrigeration power at -10°C W	465
Frequency/voltage	230V 1N~ / 50Hz
Electric power, kW	0,28
struction features	
Structure	one-piece structure with rounded internal corners
External material	special anti-fingerprint steel
Internal material	special anti-fingerprint steel
Internal bottom	with rounded corners
Insulation thickness, mm	60
Worktop	worktop 60 mm thick in AISI 304 stainless steel (8/10mm), with soundproofing lining; with splashbac
Internal structure	AISI 304 stainless steel grid-supporting rack
Positions (n.)/spaced, mm	11/40,5
Evaporator	with an anti-corrosion treatment
Easymaintenance	the cooling unit pulls out to simplify routine cleaning of the conden
Feet	stainless steel AISI 304, adjustable in height
Height of feet, mm	140 ÷ 200
Equipped with	3 doors
trol and functions	
Kinf of control	thermometer-thermostat
Display	digital
Alarms	optical
ndard	
Key-lock	optional
Shelf's dimensions, cm	32,5x53 GN1/1
Shelves and couple of guides	complete with 1 pair of AISI 304 stainless steel runners and 1 plastic-coated shelf GN1/1 per sectio

## Dim

Packing (LxDxH), cm	192x76x100
Dimensions (LxDxH), cm	185x70x98,5
Gross Weight (kg)	148
Net Weight (kg)	136



