

# KUECM



## Refrigerated counter-GN1/1-antifingerprint-Twin

All-in-one structure in special anti-fingerprint steel. Temperature ranges: 0/+10°C. Worktop 60 mm thick in AISI 304 stainless steel. Depth 70 cm. GN 1/1.4 doors. Control panel with digital thermometer - thermostat.



### General information

Supplier/producer 's name	SAGI
Series	Twin
Supplier's model identifier	KUECM
Category	counter cabinet
Type	refrigerated counter
Line	catering - GN 1/1

### Technical features

Temperature ranges, °C	0/+10
Energy Efficiency Class	C
Energy consumption, kWh/24h	3,562
Energy consumption/year, kWh/a	1300
Method for energy consumption	EN 22041
Energy Efficiency Index	49,81
Net usable volume, lt	321
Volume, gross, lt	578
Climate class	5 (+40°C, 40% R.H.)
Heavy duty cabinets	This appliance is intended for use in ambient temperatures up to 40 °C
Refrigerant/GWP	R290/3
Refrigerant charge, kg	0,08
LWA dB(A)	50
Cooling system	ventilated refrigeration system. U- flow air circulation to assure peak cooling unit reliability
Defrosting	automatic

Refrigerated counter-GN1/1-antifingerprint-Twin

ANGELO PO GRANDI CUCINE S.p.a. con socio unico  
Zona Industriale Campolungo, 79/81 - 63100 Ascoli Piceno - Italy  
[www.sagispa.it](http://www.sagispa.it) | [info@sagispa.it](mailto:info@sagispa.it)

Angelo Po S.p.a. reserves the right to make product changes and cannot be held responsible for omissions and/or errors.

1/2 PRINTED 30/04/2024 21:01:28



Evaporation of condense drain	automatic
Refrigeration power at -10°C W	560
Frequency/voltage	230V 1N~ / 50Hz
Electric power, kW	0,32

## Construction features

Structure	one-piece structure with rounded internal corners
External material	special anti-fingerprint steel
Internal material	special anti-fingerprint steel
Internal bottom	with rounded corners
Insulation thickness, mm	60
Worktop	worktop 60 mm thick in AISI 304 stainless steel (8/10mm), with soundproofing lining
Internal structure	AISI 304 stainless steel grid-supporting rack
Positions (n.)/spaced, mm	11/40,5
Evaporator	with an anti-corrosion treatment
Easymaintenance	the cooling unit pulls out to simplify routine cleaning of the condenser
Feet	stainless steel AISI 304, adjustable in height
Height of feet, mm	140 ÷ 200
Equipped with	4 doors

## Control and functions

Kinf of control	thermometer-thermostat
Display	digital
Alarms	optical

## Standard

Key-lock	optional
Shelf's dimensions, cm	32,5x53 GN1/1
Shelves and couple of guides	complete with 1 pair of AISI 304 stainless steel runners and 1 plastic-coated shelf GN1/1 per sectio

## Dimensions and weights

Packing (LxDxH), cm	235,5x75,5x90
Dimensions (LxDxH), cm	230x70x90
Gross Weight (kg)	172
Net Weight (kg)	157