

KUJBA



Refrigerated counter-Depth 60cm-Universal

One-piece AISI 304 stainless steel body. Temperature ranges: 0/+10°C. Worktop 60 mm thick in AISI 304 stainless steel with splashback 85 mm. Depth 60 cm. For shelves 32,5x46 cm. 3 doors. Control panel with digital thermometer - thermostat.



General information

| | |
|-----------------------------|------------------------|
| Supplier/producer 's name | SAGI |
| Series | Universal |
| Supplier's model identifier | KUJBA |
| Category | counter cabinet |
| Type | refrigerated counter |
| Line | catering - depth 60 cm |

Technical features

| | |
|--------------------------------|--|
| Temperature ranges, °C | 0/+10 |
| Energy Efficiency Class | C |
| Energy consumption, kWh/24h | 2,433 |
| Energy consumption/year, kWh/a | 888 |
| Method for energy consumption | EN 22041 |
| Energy Efficiency Index | 38,21 |
| Net usable volume, lt | 209 |
| Volume, gross, lt | 353 |
| Climate class | 5 (+40°C, 40% R.H.) |
| Heavy duty cabinets | This appliance is intended for use in ambient temperatures up to 40 °C |
| Refrigerant/GWP | R290/3 |
| Refrigerant charge, kg | 0,07 |
| LWA dB(A) | 50 |
| Cooling system | ventilated refrigeration system. U- flow air circulation to assure peak cooling unit reliability |
| Defrosting | automatic |

Refrigerated counter-Depth 60cm-Universal

ANGELO PO GRANDI CUCINE S.p.a. con socio unico

Zona Industriale Campolungo, 79/81 - 63100 Ascoli Piceno - Italy

www.sagispa.it | info@sagispa.it

Angelo Po S.p.a. reserves the right to make product changes and cannot be held responsible for omissions and/or errors.

1/2 PRINTED 16/05/2024 22:25:55



| | |
|--------------------------------|-----------------|
| Evaporation of condense drain | automatic |
| Refrigeration power at -10°C W | 465 |
| Frequency/voltage | 230V 1N~ / 50Hz |
| Electric power, kW | 0,28 |

Construction features

| | |
|---------------------------|---|
| Structure | one-piece structure with rounded internal corners |
| External material | AISI 304 stainless steel |
| Internal material | AISI 304 stainless steel |
| Internal bottom | with rounded corners |
| Insulation thickness, mm | 60 |
| Worktop | worktop 60 mm thick in AISI 304 stainless steel (8/10mm), with soundproofing lining; with splashbac |
| Internal structure | AISI 304 stainless steel grid-supporting rack |
| Positions (n.)/spaced, mm | 11/40,5 |
| Evaporator | with an anti-corrosion treatment |
| Easymaintenance | the cooling unit pulls out to simplify routine cleaning of the condenser |
| Feet | stainless steel AISI 304, adjustable in height |
| Height of feet, mm | 140 ÷ 200 |
| Equipped with | 3 doors |

Control and functions

| | |
|-----------------|------------------------|
| Kinf of control | thermometer-thermostat |
| Display | digital |
| Alarms | optical and acoustical |

Standard

| | |
|------------------------------|---|
| Key-lock | optional |
| Shelf's dimensions, cm | 32,5x46 |
| Shelves and couple of guides | complete with 1 pair of AISI 304 stainless steel runners and 1 plastic-coated shelf for section |

Dimensions and weights

| | |
|------------------------|-------------|
| Packing (LxDxH), cm | 192x66x100 |
| Dimensions (LxDxH), cm | 185x60x98,5 |
| Gross Weight (kg) | 138 |
| Net Weight (kg) | 126 |

Refrigerated counter-Depth 60cm-Universal