

NE150LI



Refrigerator-press-formed sides-Nex-to Plus 4.0

One-piece structure in AISI 304 stainless steel. The storage chamber consists of AISI 304 stainless steel press-formed internal sides. Fan-assisted refrigeration with external evaporator. Automatic defrosting electric type. Connectable to APO.LINK portal via Ethernet network as standard -Industry 4.0- for real time control of appliances and export and display of data log and process indicators.



General information

Supplier/producer 's name	SAGI
Series	Nex-to plus 4.0
Supplier's model identifier	NE150LI
Category	vertical cabinet
Type	refrigerator
Line	catering - GN 2/1

Technical features

Temperature ranges, °C	-2/+8
Energy Efficiency Class	B
Energy consumption, kWh/24h	1,721
Energy consumption/year, kWh/a	628
Method for energy consumption	EN 22041
Energy Efficiency Index	27,5
Net usable volume, lt	1019
Volume, gross, lt	1150
Climate class	5 (+40°C, 40% R.H.)
Heavy duty cabinets	This appliance is intended for use in ambient temperatures up to 40 °C
Refrigerant/GWP	R290/3
Refrigerant charge, kg	0,13
LWA dB(A)	51
Cooling system	ventilated refrigeration system
Defrosting	automatic by heating elements
Evaporation of condense drain	automatic

Refrigerator-press-formed sides-Nex-to Plus 4.0



NE150LI



Refrigeration power at -10°C W	533
Frequency/voltage	230V 1N~ / 50Hz
Electric power, kW	0,3

Construction features

Structure	one-piece structure with rounded internal corners
External material	AISI 304 stainless steel
Internal material	AISI 304 stainless steel
Internal bottom	diamond treated bottom
Insulation thickness, mm	75
Door	2 doors in AISI 304 stainless steel
Standard hinging door	with self-closing device for openings inferior to 90°
Door handle	integrated full-height
Internal structure	with press-formed internal sides in AISI 304 stainless steel
Positions (n.)/spaced, mm	20/55
Evaporator	positioned outside the compartment
Safety interlock switch	yes, to stop internal fan and switch on compartment light
Feet	stainless steel AISI 304, adjustable in height
Height of feet, mm	115 ÷ 165

Control and functions

Kinf of control	thermometer-thermostat RS485
Display	touch
Alarms	optical
Functions/programs	connectable to APO.LINK* portal via Ethernet for real time control of appliances

Standard

Key-lock	yes
Lighting	yes
Shelves (n.)	6+2, plastic coated + 3 plastic coated connection grids
Shelf's dimensions, cm	53x65 (GN 2/1)
Shelf loading capacity, kg	60

Dimensions and weights

Packing (LxDxH), cm	145x85,5x207
Dimensions (LxDxH), cm	139x80x204
Gross Weight (kg)	188
Net Weight (kg)	168

Notes

Notes	*export and display of data log and process indicators
-------	--------------------------------------------------------

Refrigerator-press-formed sides-Nex-to Plus 4.0

