

XE150B

Freezer-press-formed sides GN2/1-X-treme

One-piece structure in AISI 304 stainless steel. The storage chamber consists of AISI 304 stainless steel press-formed internal sides, 20 positions spaced 55cm. Single compartment, GN2/1. 2 doors. Temperature ranges: -22/-15°C. Electronic control panel. Fan-assisted refrigeration with external evaporator. High efficiency motor unit. Automatic defrosting by hot gas. Lighting and key-operated lock.



General information

| | |
|-----------------------------|-------------------|
| Supplier/producer 's name | SAGI |
| Series | X-TREME |
| Supplier's model identifier | XE150B |
| Category | vertical cabinet |
| Type | freezer |
| Line | catering - GN 2/1 |

Technical features

| | |
|--------------------------------|--|
| Temperature ranges, °C | -22/-15 |
| Energy Efficiency Class | C |
| Energy consumption, kWh/24h | 7,62 |
| Energy consumption/year, kWh/a | 2781 |
| Method for energy consumption | EN 22041 |
| Energy Efficiency Index | 42,83 |
| Net usable volume, lt | 1019 |
| Volume, gross, lt | 1150 |
| Climate class | 5 (+40°C, 40% R.H.) |
| Heavy duty cabinets | This appliance is intended for use in ambient temperatures up to 40 °C |
| Refrigerant/GWP | R290/3 |
| Refrigerant charge, kg | 0,11+0,11 |
| Cooling system | ventilated refrigeration system |
| Defrosting | automatic by hot gas |
| Evaporation of condense drain | automatic |
| Frequency/voltage | 230V 1N~ / 50Hz |

Freezer-press-formed sides GN2/1-X-treme



XE150B



| | |
|--------------------|------|
| Electric power, kW | 1,35 |
|--------------------|------|

Construction features

| | |
|---------------------------|--|
| Structure | one - piece structure with rounded internal corners |
| External material | AISI 304 stainless steel |
| Internal material | AISI 304 stainless steel |
| Internal bottom | diamond treated bottom |
| Insulation thickness, mm | 75 |
| Door | 2 doors in AISI 304 stainless steel |
| Standard hinging door | with self-closing device for openings inferior to 90° |
| Door handle | integrated full-height |
| Internal structure | with press-formed internal sides in AISI 304 stainless steel |
| Positions (n.)/spaced, mm | 20/55 |
| Evaporator | positioned outside the compartment |
| Easymaintenance | accessibility to all the functional and control components via a retractable front panel |
| Safety interlock switch | yes, to stop internal fan and switch on compartment light |
| Feet | stainless steel AISI 304, adjustable in height |
| Height of feet, mm | 115 ÷ 165 |

Control and functions

| | |
|--------------------|---|
| Kinf of control | electronic pannel control board |
| Display | digital |
| Connectivity | with APOLINK accessory for remote control - Industry 4.0 |
| Alarms | optical and acoustical |
| Functions/programs | Hyper Cold, Energy Saving and setting of the relative humidity to 75% or to 90% |

Standard

| | |
|----------------------------|--|
| Key-lock | yes |
| Lighting | yes |
| Shelves (n.) | 8 AISI 304 stainless steel 53x65cm (GN 2/1) + 2 AISI 304 stainless steel 50x62cm |
| Shelf loading capacity, kg | 60 |

Dimensions and weights

| | |
|------------------------|--------------|
| Packing (LxDxH), cm | 145x85,5x207 |
| Dimensions (LxDxH), cm | 139x80x204 |
| Gross Weight (kg) | 230 |
| Net Weight (kg) | 210 |

Freezer-press-formed sides GN2/1-X-treme

